

	CONTACT	DWELLIN	IG UNIT MATRIX	
HIS STORE AND	OWNER: ARCHITECT: CIVIL	DWELLING UNIT #	# OF BEDROOMS	DWELLING UNIT S.F.
	PISANI PL LP.BREAKFORM DESIGNOBAN2999 OVERLAND AVE, #130109 EUCALYPTUS DR.1453 7	DO & ASSOCIATES, INC. 1A I4TH ST. STE. A MARKET RATE	1 BED / 1 BATH	485 S.F.
	Т. 310 306 3504 Т. 310 322 3700 Т. 310	A MONICA, CA 90404 821 7555 821 7491 MARKET RATE	1 BED / 1 BATH	488 S.F.
HIT DED HIT DE	LANDSCAPE ARCHITECT: STRUCTURAL ENGINEER: BREAKFORM DESIGN JOHN LABIB & ASSOCIATES	1C VERY LOW INCOME	1 BED / 1 BATH	515 S.F.
	EL SEGUNDO, CA 90245 EL SEGUNDO, CA 90245 FLOR	ENGINEER: 2A ES ENGINEERING MARKET RATE	2 BED / 2.5 BATH	1,833 S.F.
	F. 213 239 9699 LOS A	SPERANZA ST 3A NGELES, CA 90023 MARKET RATE 727 6066	3 BED / 3.5 BATH	2,025 S.F.
PROJECT PROJECT	SURVEY:SOILS ENGINEER:LAWRENCE J. SCHMAHLIRVINE GEOTECHNICAL INC.11209 HOWARD ST.145 N SIERRA MADRE BLVD SUIT 12	3B MARKET RATE	3 BED / 3.5 BATH	2,025 S.F.
	11209 HOWARD S1. 145 N SIERRA MADRE BLVD S01 12 WHITTIER, CA 90606 PASADENA, CA 91107 T. 562 908 0570 T. 626 844 6641	4A MARKET RATE	3 BED / 3.5 BATH	2,025 S.F.
	F. 323 773 1675 F. 626 604 0394	4B MARKET RATE	3 BED / 3.5 BATH	2,025 S.F.
CODE	SYMBOLS	TOTAL DWELLING UNIT S.F.		11,421 S.F.
BUILDING CODE: 2017 LABC, (TITLE 24, PART 2.5)	Матсні		GMATRIX	
BASED ON THE 2009 IRC (INCLUDES ACCESSIBILITY) STRUCTURAL: 2017 LABC, VOL 2 (TITLE 24, PART 2, VOL 2)	AC	CENTER LINE FLOOR	ROOM	AREA
BASED ON THE 2009 IBC WITH ASCE7-05 MECHANICAL CODE: 2016 CA MECHANICAL CODE, (TITLE 24, PART 4)	BUILDING WALL SECTION SECTION	GRIDLINE PROJECTION 1 ST ABOVE/BELOW	LOBBY	307 S.F.
BASED ON THE 2009 UNIFORM PLUMBING CODE PLUMBING CODE: 2016 CA PLUMBING CODE (TITLE 24, PART 5)	INDICATES A JOG IN THE BUILDING SECTION	BREAK LINE 1 ST	STAIR A-1	130 S.F.
BASED ON THE 2009 UNIFORM PLUMBING CODE	(0,0,0) COORDINATE PROJECT GRID	REVISION SYMBOL 1 ST	STAIR A-2	130 S.F.
ELECTRICAL CODE: 2016 CA ELECTRICAL CODE (TITLE 24, PART 3) BASED ON THE 2008 NATIONAL ELECTRIC CODE	DETAIL AREA	BUILDING ELEVATION	BIKE STORAGE	155 S.F.
ENERGY CODE: 2016 CA ENERGY CODE (TITLE 24, PART 6) 2017 L.A. CITY GREEN BUILDING CODE	ROOM SYMBOL	1 ST	RECYCLING / TRASH	70 S.F.
	DOOR SYMBOL	1 ST	GARAGE	2,433 S.F.
	BASEMENT FF + 491.0° DATUM	A3.1.2 4 ELEVATION SYMBOLS 3 RD	COMMON HALLWAY	175 S.F.
	WINDOW SYMBOL WP WORK POINT	4 TH	COMMON HALLWAY	175 S.F.
		TOTAL S.F.		3,575 S.F.
		TOTAL BUILDING S.F.	11,447 S.F. + 3,612 S.F.	= 15,016 S.F.
Ø Diameter or Round CONC Concrete F. Ø Perpendicular CONST Construction F. L Perpendicular CONST Construction F. CDNT Continuous FL CONTR Continuous FL (E) Existing CONTR Contractor FL AB Anchor Bolt C.T. Ceramic Tile F. A/C Air Conditioning CTR Contresunk F. AC Asphaltic Concrete CTSK Countersunk F. ACT Acoustical FF ACOUS Accoustical FF ALT Alter or Alternate DE Deep, Depth FF ALUM Aluminum D.F. Drinking Fountain FI ANOD Anodized DIA Diameter FL APPROX Approximate DISP Dispenser FL ARCH Architectural DN Down G G BLG Blocking DS Downspout G G <td>D. Floor Drain INCL Including N Foundation INSUL Insulation E. Fire Extinguisher Cab G. Fine Extinguisher Cab G. Finish Grade JAN Janitor H.C. Fire Hose Cabinet JST Joist N Finish ASH Flashing R Floor KIT Kitchen UOR Fluorescent O.C. Face of Concrete LAM Laminate O.F. Face of Finish LAV Lavatory O.M. Face of Masonry L.F. Lineal Foot O.S. Face of Stud L.H. Left Hand PRF Fireproof LKR Locker R Full Size LT Light Frame L.R. Living Room S Full Size LT Light T G Footing JRR Furring, Furred MATL Material JT Future MAX Maximum M.B. Machine Ball A Gauge MECH Mechanical ALV Galvinized Iron MFR Manufacture A Gauge MECH Mechanical ALV Galvinized Iron MFR Manufacture J. Glass, Glazing MH Manufacture M.B. Molecture M.B. Molecture M.B. Molecture M.B. Molecture M.B. Machine Ball M. Gause MIR MIR Minimum R Grade MIR MIR Minimum R Grade MIR Minimum A Grade MIR Mirror YP Gypsum MISC Miscellaneous M.D. Masterial B. Hose Bib MTD Mounted C. Hollow Core MUL Mullion CP Handware N N North DWD Hardware N N</td> <td>O.D.Outside DiameterO.F.D.Overflow DrainOFFOfficeO.H.OverhangOVHDOverheadOPNGOpeningOPPOppositePCPieceP.D.Planter DrainPLPlateP.L.Property LinePLMGPlumbingPLAMPlastic LaminatePLASPlasterPLYWDPlywoodPRPairPTPaintP.T.D.Paper Towel DispenserPTNPatitionQ.T.Quarry TileRRiserRADRadiusR.D.Roof DrainREFRefrigeratorREINFReinforced or ReinforcingREQRequiredRESILResilientREVRevisedRFGRoofingR.H.Right HandRMRoomR.O.Rough OpeningRWDRedwoodSSouthS.C.Solid CoreSCHEDScheduleSEPSeparation, SeparateSHTSheet</td> <td>SIMSimilarWSLDGSidingW/SPECSpecificationW.H.SQSquareW/OS.S.Stainless SteelW.C.SSKService SinkWDSTDStandardWPSTDStandardWPSTLSteelWPMSTORStorageWSCTSTRUCTStructrualW.S.P.SUSPSuspendedWTSWSwitchSYMSymmetricalSYSSystemTTreadT.B.Towel BarT&GTop of DrainTELTelephoneTEMPTempered, TemperatureTERTerrazzoTHKThick, ThicknessTHRTrick ThicknessTRGTop of StabT.P.D.Top of SteelTVTelevisionT.O.W.Top of WallTYPTypicalUNFUnfinishedU.O.N.Unless Otherwise NotedURUrinalVERTVerticalVESTVestibuleV.I.F.Vertify in FieldVOLVolume</td> <td>West With Water Heater Without Water Closet Wood Waterproof Membrane Wainscot Wet Standpipe Weight</td>	D. Floor Drain INCL Including N Foundation INSUL Insulation E. Fire Extinguisher Cab G. Fine Extinguisher Cab G. Finish Grade JAN Janitor H.C. Fire Hose Cabinet JST Joist N Finish ASH Flashing R Floor KIT Kitchen UOR Fluorescent O.C. Face of Concrete LAM Laminate O.F. Face of Finish LAV Lavatory O.M. Face of Masonry L.F. Lineal Foot O.S. Face of Stud L.H. Left Hand PRF Fireproof LKR Locker R Full Size LT Light Frame L.R. Living Room S Full Size LT Light T G Footing JRR Furring, Furred MATL Material JT Future MAX Maximum M.B. Machine Ball A Gauge MECH Mechanical ALV Galvinized Iron MFR Manufacture A Gauge MECH Mechanical ALV Galvinized Iron MFR Manufacture J. Glass, Glazing MH Manufacture M.B. Molecture M.B. Molecture M.B. Molecture M.B. Molecture M.B. Machine Ball M. Gause MIR MIR Minimum R Grade MIR MIR Minimum R Grade MIR Minimum A Grade MIR Mirror YP Gypsum MISC Miscellaneous M.D. Masterial B. Hose Bib MTD Mounted C. Hollow Core MUL Mullion CP Handware N N North DWD Hardware N N	O.D.Outside DiameterO.F.D.Overflow DrainOFFOfficeO.H.OverhangOVHDOverheadOPNGOpeningOPPOppositePCPieceP.D.Planter DrainPLPlateP.L.Property LinePLMGPlumbingPLAMPlastic LaminatePLASPlasterPLYWDPlywoodPRPairPTPaintP.T.D.Paper Towel DispenserPTNPatitionQ.T.Quarry TileRRiserRADRadiusR.D.Roof DrainREFRefrigeratorREINFReinforced or ReinforcingREQRequiredRESILResilientREVRevisedRFGRoofingR.H.Right HandRMRoomR.O.Rough OpeningRWDRedwoodSSouthS.C.Solid CoreSCHEDScheduleSEPSeparation, SeparateSHTSheet	SIMSimilarWSLDGSidingW/SPECSpecificationW.H.SQSquareW/OS.S.Stainless SteelW.C.SSKService SinkWDSTDStandardWPSTDStandardWPSTLSteelWPMSTORStorageWSCTSTRUCTStructrualW.S.P.SUSPSuspendedWTSWSwitchSYMSymmetricalSYSSystemTTreadT.B.Towel BarT>op of DrainTELTelephoneTEMPTempered, TemperatureTERTerrazzoTHKThick, ThicknessTHRTrick ThicknessTRGTop of StabT.P.D.Top of SteelTVTelevisionT.O.W.Top of WallTYPTypicalUNFUnfinishedU.O.N.Unless Otherwise NotedURUrinalVERTVerticalVESTVestibuleV.I.F.Vertify in FieldVOLVolume	West With Water Heater Without Water Closet Wood Waterproof Membrane Wainscot Wet Standpipe Weight

SF CALC	S BY CODE
ZONING CODE :	
1ST FLOOR 2ND FLOOR 3RD FLOOR 4TH FLOOR	1,494 SF 1,853 SF 4,050 SF 4,050 SF
TOTAL	11,447 SF
(SEE PAGE A0.4	11 FOR BREAKDOWN)
BUILDING CODE:	
1ST FLOOR -COVERED -LOBBY -GARAGE 2ND FLOOR -COVERED 3RD FLOOR -COVERED -LOBBY 4TH FLOOR -COVERED -LOBBY	1,494 SF 288 SF 284 SF 2,433 SF 1,853 SF 28 SF 4,050 SF 513 SF 175 SF 4,050 SF 253 SF 175 SF
TOTAL	15,596 SF
(SEE PAGE A0.4	42 FOR BREAKDOWN)

YARD

THIS PROJECT IS 100% PRIVATELY FUNDED. NO TAX CREDITS OR INCENTIVES WERE RECEIVED. THIS PROJECT IS NOT PUBLIC HOUSING.

SHR SHT Shower Sheet

	SIM SLDG SPEC SQ S.S. SSK STD STL STOR STRUG SUSP SW SYM SYS
enser nforcing	T T.B. T&G T.O.C. T.O.D. TEL TEMP TER THK THR TOIL T.O.P. T.O.S. T.P.D. T.S. TV T.O.W TYP
	UNF U.O.N. UR
	VERT VEST V.I.F. VOL







PROJECT SUMMARY:	NEW 8-UNIT MULTI-FAMILY RE STORY BUILDING WITH PARK *UTILIZING INCENTIVES PER I	ING.
SCOPE OF WORK:	NEW FOUNDATION, STRUCTU CONSTRUCTION (MECHANIC/ PLUMBING) OF NEW 8 UNIT M RESIDENCES.	AL / ELECTRICAL /
PROJECT ADDRESS:	2308 PISANI PLACE, VENICE, (CA 90291
NET LOT AREA (AFTER DEDICATIONS):	7,800 S.F.	
ZONE:	R3-1	
NUMBER OF STORIES:	FOUR (4)	
MAX HEIGHT:	41'-0" W/ VARIED ROOF, 36'-0"	' FLAT
TOTAL PARKING:	12 SPACES	
TRACT:	VENICE GATEWAY	
BLOCK:	Ν	
LOT:	14, 15	
ASSESSOR PARCEL NUMBER (APN):	4237005010	
GROSS LOT AREA:	8,000 S.F.	
BUILDABLE LOT AREA:	5,425 S.F.	
RESIDENTIAL S.F.:	11,447 S.F.	
PARKING S.F.:	2,433 S.F.	
PROJECT TOTAL S.F.:	15,016 S.F.	
NUMBER OF DWELLING UNITS:	EIGHT (8)	
OPEN SPACE S.F.:	1,615 S.F.	
CONSTRUCTION TYPE:	TYPE V-A	<u>NOTE:</u> THIS BUILDING SHALL BE PROVIDED WITH A MANUAL ALARM SYSTEM WITTH THE CAPABILITY T
SPRINKLER:	NFPA-13	SUPPORT VISIBLE ALARM NOTIFICATION APPLIANC IN ACCORDANCE WITH NFPA 72

ALLOWED

		///////////////////////////////////////	
RESIDENTIAL: Common Bldg: (Lobby, common Hallways	11,421 S.F. 727 S.F. S, TRASH)	SITE BUILDABLE AREA = 16,275 (80' - 5' - 5') x (107'-6" - 15' - 15') : (LOT WIDTH - SIDE YARD SETB SET BACKS) F.A.R. ALLOWED: 3:1 (3) 5,425 = 16,275 S.F.	
TOTAL:	12,148 S.F.	TOTAL:	16,275 S.F.
		ED VS. ALLOV	
41' - 0" VARIED ROOF		30' VARIED ROOF	
36' - 0" FLAT ROOF		25' FLAT ROOF	
DENSITY	PROVIDED V	S. ALLOWED	
PROVIDED		ALLOWED	
DWELLING UNITS:	8 DWELLING UNITS	GROSS LOT AREA:	8,000 S.F.
		(GROSSLOTAREA) / 800 = 10	

PARKING		/S. REQUIRE	D	
TOTAL PROVIDED:	8 DWELLING UNITS	TOTAL ALLOWED:	10 DWELLING UNITS	
		(GROSS LOT AREA) / 800 = 1	0	

PROVIDED		REQUIRED	
TENANT PARKING: (10% PARKING REDUCTION USIN TERM BICYCLE SPACES IN LIEU	12 SPACES (5 COMPACT, 6 STANDARD, 1 ADA) IG THE BICYCLE ORDINACE (USING 4 LONG OF ONE CAR PARKING SPACE))	TENANT PARKING: 1 SPACES PER 0-1 BD UNITS 2 SPACES PER 2-3 BD UNITS 2.5 SPACES PER 4+ BD UNITS *NO GUEST SPACES REQ.* = 13 SPACES REQ. 13 SPACES - <u>10% BICYCLE REDU</u>	NOTE: PARKING REQUIRED IS CALCULATED PER; 12.22A.25, PARKING OPTION 1, AND BICYCLE REPLACEMENT. I <u>CTION</u> = 12 SPACES "UNBUNDLED"
TOTAL PROVIDED:	12 SPACES	TOTAL REQUIRED:	12 SPACES

BICYCLE PARKING PROVIDED VS. REQUIRED PROVIDED REQUIRED 16 SPACES LONG TERM BICYCLE PARKING: (ONE SPACE PER. UNIT) 8 SPACES LONG TERM BICYCLE PARKING: SHORT TERM BICYCLE PARKING: 2 SPACES 2 SPACES SHORT TERM BICYCLE PARKING: (ONE PER 10 DWELLING UNITS(MIN. 2 SPACES))

TOTAL LONG TERM PROVIDED: 16 SPACES TOTAL LONG REQ .: 8 SPACES 2 SPACES TOTAL SHORT TERM PROVIDED: 2 SPACES TOTAL SHORT TERM PROVIDED: YARD SETBACK PROVIDED VS. REQUIRED PROVIDED REQUIRED WEST SIDE YARD 7' - 0" 7' - 0" @ ALL LEVELS

			_
PISANI PL. FRONT YARD	12' - 0"		15' - 0" @ ALL LEVELS
ALLEY REAR YARD	14' - 6" FROM C.L. OF ALLEY		15' - 0" FROM C.L. OF ALLEY@ ALL LEVELS
EAST SIDE YARD	7' - 0" @ ALL LEVELS		7' - 0" @ ALL LEVELS
OPEN SPACE	PROVIDED	VS. R	EQUIRED
PROVIDED		REQUIRED	
OPEN SPACE BREAKDOWN:			1 BEDROOMS: 100 SF X 3 = 300 SF
COMMON OPEN SPACE:	1.415 S.F.		2 BEDROOMS: 125 SF X 1 = 125 SF 3 BEDROOMS: 175 SF X 4 = 700 SF

••••••••	.,		
USABLE PRIVATE OPEN SPACE TOWARDS CALCULATION BASED ON ZONING CODE 12.21 G:	200 S.F.		
TOTAL PROVIDED OPEN SPACE:	1,615 S.F.	TOTAL REQUIRED OPEN SPACE:	1,125 S.F.

INCENTIVES & WAIVERS / MODIFICATIONS

ON- AND OFF-MENU DEVELOPMENT INCENTIVES 12.22 A 25 (F):

ALLOW A 14'-6" REAR YARD SETBACK IN LIEU OF A 15'-0" REQUIRED REAR YARD SETBACK PURSUANT TO LAMC 12.09 B 3, REPRESENTING A 3% REDUCTION IN REQUIRED REAR YARD SETBACK.

ALLOW AN 11' INCREASE IN HEIGHT TO COMPLETE A 41' MAXIMUM VARIED ROOF HEIGHT AND A 36' MAXIMUM FLAT ROOF HEIGHT PERMITTED PURSUANT TO THE VENICE COASTAL ZONE SPECIFIC PLAN SECTION 10.G.3.


ALLOW AN 11'-11" FRONT YARD SETBACK IN LIEU OF A 15'-0" REQUIRED FRONT YARD SETBACK PURSUANT TO LAMC 12.09 B 1, REPRESENTING A 21% REDUCTION IN REQUIRED FRONT YARD SETBACK. WAIVERS OF DEVELOPMENT STANDARDS:

ALLOW THREE (3) ROOF ACCESS STRUCTURES: TWO (2) ACCESS STRUCTURES FOR ROOF STAIR AND ONE (1) ROOF ACCESS STRUCTURE FOR ELEVATOR IN LIEU OF THE SÍNGLE ROOF ACCESS STRUCTURE PÈRMITTED PURSUANT TO THE VENICE COASTAL ZONE SPECIFIC PLAN. PERMIT 7 PARKING STALLS TO BE PROVIDED AS STANDARD STALLS AND 5 SPACES TO BE PROVIDED AS COMPACT STALLS IN LIEU OF THE MINIMUM 8

STANDARD PARKING STALLS REQUIRED PURSUANT TO LAMC 12.21 A 5(C).

PERMIT 7 UNITS TO HAVE ACCESS TO PARKING STALLS IN LIEU OF 8 UNITS PER THE REQUIREMENT FOR EACH REQUIRED PARKING STALL WITHIN A PARKING AREA TO BE ACCESSIBLE PURSUANT TO LAMC 12.21 A 5(H).

Sheet	SHEET INDEX
	Sheet Name
_	ECTURAL
A0.01	
A0.02	VENICE SIGN-OFF
A0.03 A0.04	GREEN FORMS SPECS / RESEARCH REPORTS
A0.04 A0.05	SPECS / RESEARCH REPORTS
A0.05 A0.06	SPECS / RESEARCH REPORTS
A0.00	SPECS / RESEARCH REPORTS
A0.08	SPECS / RESEARCH REPORTS
A0.10	WALL & FLOOR TYPES
A0.11	DOOR SCHEDULE
A0.12	WINDOW SCHEDULE
A0.13	GENERAL DETAILS
A0.14	GENERAL DETAILS
A0.15	WINDOW DETAILS
A0.16	WINDOW DETAILS
A0.17	DOOR DETAILS
A0.18	ACCESSIBILITY NOTES
A0.19	ACCESSIBILITY DETAILS
A0.20	ACCESSIBILITY DETAILS
A0.21	TITLE 24
A0.22	TITLE 24
A0.23	
A0.24	
A0.25	EXISTING SITE SURVEY
A0.26	
A0.27	SLAB PLAN
A0.28 A0.40	SLAB PLAN OPEN SPACE & FAR BUILDABLE AREA
A0.40 A0.41	ZONING CODE SF
A0.41 A0.42	BUILDING CODE SF
A0.42	SITE PLAN
A2.10	1ST FLOOR / PARKING
A2.20	2ND FLOOR PLAN
A2.30	3RD FLOOR PLAN
A2.40	4TH FLOOR PLAN
A2.50	ROOF PLAN
A3.10	ELEVATIONS
A3.20	ELEVATIONS
A3.30	ELEVATIONS
A3.40	ELEVATIONS
A4.10	PROPOSED SECTIONS
A4.20	PROPOSED SECTIONS
A4.30	PROPOSED SECTIONS
A4.40	PROPOSED SECTIONS
A4.50	PROPOSED SECTIONS
A4.60	PROPOSED SECTIONS
A4.70	DRIVEWAY SECTIONS
A5.10	ENLARGED PLANS
A5.20 A5.30	ENLARGED PLANS ENLARGED PLANS
A5.30 A7.10	REFLECTED CEILING LEVEL 1
A7.10 A7.11	LIGHT SCHEDULE - LEVEL 1
A7.11 A7.20	REFLECTED CEILING LEVEL 2
A7.20 A7.21	LIGHT SCHEDULE - LEVEL 2
A7.30	REFLECTED CEILING LEVEL 3
A7.30	LIGHT SCHEDULE - LEVEL 3
A7.40	REFLECTED CEILING LEVEL 4
A7.41	LIGHT SCHEDULE - LEVEL 4
A9.00	VERTICAL CIRCULATION
A9.10	VERTICAL CIRCULATION
A9.20	EXTERIOR STAIRS
	DETAILS - EXTERIOR
A9.40	
A9.40 A9.50	DETAILS - DOORS & WINDOWS



Park-It 2-Bike Racks/ 2- Ks by TreeTop Products Bike Rack/ Surface Mount/ Black

- DESCRIPTION
- Perfect solution to customize your bike parking area.

• Capacity: 2 56

- Security: 🔗 🎸 🎸
- One of our most popular choices among parks and municipalities
- Two points of contact to stabilize & lock two bikes
- 1-7/8" OD 11-gauge round steel tubing
- Powder-coated steel in Black Onyx
- Choose surface mount or inground mount
- noose optional set of steel Surface Mount Covers to conceal mounting hardware

CUMENTS AND INSTRUCTIONS

- Inground Mount Installation Instructions [Size: 73.6 KB]
- Inground Mount Specifications [Size: 141.8 KB]
- Surface Mount Specifications [Size: 241 KB]
- Surface Mounting Instructions [Size: 76.4 KB]


SPECIFICATIONS

SKU	7ZT7074	7ZT7083
Model Name	Surface Mount 2-Bike Rack - Black	Inground Mount 2-Bike Rack - Black
Material	Steel	Steel


/2021	Park-It 2-Bike Racks P	ark It Bike Racks by TreeTop Produc
Mount Type	Surface Mount	Inground
Bike Capacity	2	2
Frame Tube Diameter	1 7/8"	1 7/8"
Length	22"	22"
Height	36"	36"
Weight	17.000000	18.000000



© 2019 Copyright Park It Bike Racks, All rights reserved.




🏭 securabike.com.au






	81-94- 21	1989 1999 98884 2
	A.C IND	ICATES ASPHALT CONCRETE PAVEMENT
	C.F.O IN	NDICATES CURB FACE OUTLET (DRAINAGE)
	F.S IND	ICATES FINISHED SURFACE
	T.C IND	CATES TOP OF CURB
	F.L INDI	CATES FLOW LINE
	F.G INDICATE	ES FINISHED GRADE
	W.M INDI	CATES WATER METER
	W.I INI	DICATES WROUGHT IRON
	CONC INDICA	TES CONCRETE
		DICATES CONC. BLOCK WALL
		NDICATES POURED CONC. RETAINING WALL
	C.B.R.W I FNC INDI	NDICATES CONC. BLOCK RETAINING WALL
		ATES FINISH FLOOR
	G.B INDICA	TES GRADE BREAK
	E.M INDIC	CATES ELECTRIC METER
	G.M INDI	CATES GAS METER
	T.G INDIC	ATES TOP OF GRATE (DRAIN)
	W.I.G I	NDICATES WROUGHT IRON GATE
		DICATES PIPE INVERT
100.97		NDICATES DECIDUOUS TREE
EP	EUC IM	NDICATES EUCALYPTUS TREE
100.88 WV		INDICATES CONCRETE SURFACE
100.69 AC	(P.P.)	. INDICATES POWER POLE
100.48		
FL AC		. INDICATES LIGHT POLE
101.20 EP	40"Ø	. INDICATES TREE AND TRUNK DIAMETER
	////	. INDICATES WOOD FENCE
		. INDICATES CHAIN-LINK FENCE
		INDICATES SANITARY SEWER LINE
	TOPOGRAPHIC	NOTES
	1. CONTOUR LINES SHOWN ON TH WERE GENERATED FROM RANDO EXPECTED LEVEL OF ACCURACY INTERVAL. ISOLATED ELEVATIONS WERE PHYSICALLY MEASURED A LOCATIONS SHOWN. THEIR EXPE IS \pm 0.10 FOOT.	M SPOT ELEVATIONS. THE IS ±1/2 OF THE CONTOUR , AS PLACED ON THE PLAT T APPROXIMATELY THE
	2. IF SPECIFIC ELEVATIONS ARE R CONTACT PIAL ENGINEERING, INO SAME. INTERPOLATIONS MADE SURVEY SHOULD BE DONE IN A ENGINEERING PRACTICE, AND LI IS NOT ASSUMED BY THE PREF	C., TEL: (310)379–4941 FOR FROM THIS TOPOGRAPHIC ACCORDANCE WITH STANDARD ABILITY FOR INTERPOLATIONS
	LEGAL DESC	RIPTION
	LOTS 14 & 15 IN BLOCK N OF VENIC OF LOS ANGELES, COUNTY OF LOS A	
	AREA = 8,000.85 SQ. FT.	
	SURVEY CERTI	FICATION
	I HEREBY CERTIFY THAT I AM A REGIST STATE OF CALIFORNIA, THAT THIS PLAT CORRECTLY REPRESENTS A SURVEY MAI MARCH, 2015; THAT ALL MONUMENTS S AND THEIR POSITIONS ARE CORRECTLY NOT INCLUDE EASEMENTS EXCEPT THOS HEREON.	CONSISTING OF ONE SHEET DE UNDER MY SUPERVISION IN SHOWN HEREON ACTUALLY EXIST SHOWN. THIS SURVEY DOES
	CHRISTOPHER W. VASSALLO P.L.S. 8418 EXPIRES 12/31/20	
	LOT & TOPOGRA	PHIC SURVEY
	CLIENT	FILE NAME: DATE: $04 - 08 - 2015$ 10 - 01 - 2020(RV)
E: 1/8"=1'-0"	PISANI PLACE, LP	$\frac{10-01-2020(RV)}{SCALE: 1/8"-1'-0"}$
terrer terrer etter state atte	DRAWN DV. PROJECT SITE:	SCALE: 1/8"=1'-0"
	I PROTECT NUE	
	DRAWN BY: JAL/AP LOS ANGELES, CA 90	


LEGEND





HARDSCAPE 2




E PROVID	ED VS. RE
	REQUIRED
1,415 S.F.	(3) UNITS WITH 1 BEDI (1) UNITS WITH 2 BEDI (4) UNITS WITH 3 BEDI
200 S.F.	
1,615 S.F.	TOTAL REQUIRED OPE
	1,415 S.F. 200 S.F.







4





RESIDENTIAL			HATCH
DWELLING UNIT #	# OF BEDROOMS	DWELLING UNIT S.F.	
1A	1 BED / 1 BATH	485 S.F.	
1B	1 BED / 1 BATH	488 S.F.	
1C	1 BED / 1 BATH	515 S.F.	
2A	2 BED / 2.5 BATH	1,833 S.F.	
3A	3 BED / 3.5 BATH	2,025 S.F.	
3B	3 BED / 3.5 BATH	2,025 S.F.	
4A	3 BED / 3.5 BATH	2,025 S.F.	
4B	3 BED / 3.5 BATH	2,025 S.F.	
		TOTAL = 11,421 S.F.	
BUILDING MATE	RIX		
FLOOR	ROOM	AREA	
1 ST	LOBBY	307 S.F.	
1 ST	RECYCLING / TRASH	70 S.F.	
3 RD	COMMON HALLWAY	175 S.F.	
4 TH	COMMON HALLWAY	175 S.F.	


NOT COUNTED TOWARDS ZONING CODE SF

1 ST	STAIR A-1	130 S.F.	
1 ST	STAIR A-2	130 S.F.	
1 ST	BIKE STORAGE	155 S.F.	
1 ST	GARAGE	2,433 S.F.	


TOTAL = 727 S.F.

















RESIDENTIAL		<u>15,578 SF</u>
ELLING UNIT #	# OF BEDROOMS	DWELLING UNIT S.F.
1A	1 BED / 1 BATH	485 S.F.
1B	1 BED / 1 BATH	488 S.F.
1C	1 BED / 1 BATH	515 S.F.
2A	2 BED / 2.5 BATH	1,833 S.F.
3A	3 BED / 3.5 BATH	2,025 S.F.
3B	3 BED / 3.5 BATH	2,025 S.F.
4A	3 BED / 3.5 BATH	2,025 S.F.
4B	3 BED / 3.5 BATH	2,025 S.F.
		TOTAL = 11,421 S.F.
BUILDING MATI	RIX	
FLOOR	ROOM	AREA
1 ST	GARAGE	2,433 S.F.
1 ST	LOBBY'S	284 S.F.
1 ST	COVERED AREA	142 S.F.
2 ND	COVERED AREA	28 S.F.
3 RD	COMMON HALLWAY	175 S.F.
3 RD	COVERED AREA	513 S.F.
4 TH	COMMON HALLWAY	175 S.F.
4 TH	COVERED AREA	235 S.F.


NOT COUNTED TOWARDS	BUILDING CODE SF	
1 ST	STAIR A-1	130 S.F.
1 ST	STAIR A-2	130 S.F.
1 ST	BIKE STORAGE	155 S.F.
1 ST	RECYCLING / TRASH	70 S.F.








N N




4TH FLOOR - BUILDING CODE SF 1/8" = 1'-0"






3RD FLOOR - BUILDING CODE SF 1/8" = 1'-0" 3







	ASSEMBLY	TYPES	
WAI	LS	<u>FLOO</u>	URS
$\langle 1 \rangle$	12" CONC. PER STRC.	A-1	CONC FLOOR PER STRC. W/ WOOD FINISH
2>	8" CMU PER STRC.	A-2>	CONC FLOOR PER STRC. W/ TILE FINISH
3	1HR 2X6 EXTERIOR WALL ASSM.	(A-3)	CONC FLOOR PER STRC. W/ POLISHED CONC. FINISH
$\langle 4 \rangle$	2X6 EXTERIOR WALL ASSM.	B-1	WOOD JOIST PER STRC. W/ WOOD FINISH
5	2X4 & 2X6 INTERIOR WALL ASSM.	B-2>	WOOD JOIST PER STRC. W/ TILE FINISH
6	2X6 PLUMBING WALL ASSM.	R-1	WOOD JOIST W/ WOOD DECK PER SPEC.
$\langle 7 \rangle$	1 HR DBL. 2x4 INTERIOR WALL ASSM.	R-2>	WOOD JOIST PER STRC. W/ METAL ROOFING PER SPEC.
8	2 HR 2x6 VERTICAL EXIT ENCLOSURE WALL ASSM.		
\wedge			


9	10" CONC. PER STRC.	


FLOOR PLAN LEGEND

«	FLOOR TYPE
	1 HR
	2 HR
SD	SMOKE DETE
	CARBON MON
	EXHAUST (GENERAL NO
X	WINDOW TAG
XXX	DOOR TAG
×	WALL TYPE
<u>-X'-X"</u>	ELEVATION M
	PROPERTY LI

ECTOR ONOXIDE NOTES #2,3) MARKER

 $\rightarrow - \rightarrow -$ ACCESSIBLE ROUTE





1ST FLOOR 1/4" = 1'-0"

ASSEMBLY	TYPES

WAL	LS
	12" CONC. PER STRC.

- 2 8" CMU PER STRC.
- 1HR 2X6 EXTERIOR WALL ASSM. $\langle 3 \rangle$
- $\langle 4 \rangle$ 2X6 EXTERIOR WALL ASSM.
- 5 2X4 & 2X6 INTERIOR WALL ASSM.
- (6) 2X6 PLUMBING WALL ASSM.
- 1 HR DBL. 2x4 INTERIOR WALL ASSM.
- 2 HR 2x6 VERTICAL EXIT
ENCLOSURE WALL ASSM.
- 9 10" CONC. PER STRC.

FLOOR PLAN LEGEND

~×~~°	FLOOR TYPE
	1 HR
	2 HR
SD	SMOKE DETECTO
	CARBON MONOXI
	EXHAUST (GENERAL NOTES WINDOW TAG
X	
(XXX)	DOOR TAG
×	WALL TYPE
<u>- X'-X"</u>	ELEVATION MARK
	PROPERTY LINE

E DETECTOR ON MONOXIDE JST ERAL NOTES #2,3) OW TAG YPE ATION MARKER

 $\rightarrow - \rightarrow -$ ACCESSIBLE ROUTE


- FINISH
- A-2 CONC FLOOR PER STRC. W/ TILE FINISH
- CONC FLOOR PER STRC. W/ POLISHED CONC. FINISH (A-3)
- WOOD JOIST PER STRC. W/ WOOD <**B**-1⟩ FINISH
- WOOD JOIST PER STRC. W/ TILE FINISH <В-2>
- (R-1)
- WOOD JOIST W/ WOOD DECK PER SPEC. WOOD JOIST PER STRC. W/ METAL ROOFING PER SPEC.
- ΄ Α


(**B**

(C)

A3.30 1

(E)-







2ND FLOOR 1/4" = 1'-0"


		ASSEMBLY T	YPES			, 7' -
WAL	LS		<u>FLOC</u>	<u>PRS</u>		
$\langle 1 \rangle$	12" CONC.	PER STRC.	(A-1)	CONC FLOOR PER STRC. W/ WOOD FINISH		
2>	8" CMU PE	R STRC.	A-2>	CONC FLOOR PER STRC. W/ TILE FINISH		l
$\langle 3 \rangle$	1HR 2X6 E	XTERIOR WALL ASSM.	(A-3)	CONC FLOOR PER STRC. W/ POLISHED CONC. FINISH		
$\langle 4 \rangle$	2X6 EXTER	RIOR WALL ASSM.	B-1	WOOD JOIST PER STRC. W/ WOOD FINISH		4' - 6"
5	2X4 & 2X6 ASSM.	INTERIOR WALL	B-2>	WOOD JOIST PER STRC. W/ TILE FINISH		
	2X6 PLUM	BING WALL ASSM.	(R-1)	WOOD JOIST W/ WOOD DECK PER SPEC.	(A)	
$\langle 7 \rangle$	1 HR DBL. WALL ASS	2x4 INTERIOR M.	R-2	WOOD JOIST PER STRC. W/ METAL ROOFING PER SPEC.		
< <u>8</u> >		'ERTICAL EXIT RE WALL ASSM.				I I
(9)		PER STRC.				
	FLOOR	PLAN LEGEND				11'- 8 1/2"
6	-x-~°	FLOOR TYPE				
		1 HR				
		2 HR				م
	SD	SMOKE DETECTOR				2 C
	(<u>CM</u>)	CARBON MONOXIDE				
		EXHAUST (GENERAL NOTES #2,3)				
	X	WINDOW TAG				
(XXX	DOOR TAG				
~	×	WALL TYPE				


X'-X" ELEVATION MARKER


 \rightarrow — \rightarrow — ACCESSIBLE ROUTE













2' - 6" DJECTION



1 A3.10




3RD FLOOR 1/4" = 1'-0"

ASSEMBLY TYPES				
WAL	LS	<u>FL00</u>	RS	
$\langle 1 \rangle$	12" CONC. PER STRC.	(A-1)	CONC FLOOR PER STRC. W/ WOOD FINISH	
2>	8" CMU PER STRC.	A-2>	CONC FLOOR PER STRC. W/ TILE FINISH	
3>	1HR 2X6 EXTERIOR WALL ASSM.	A-3>	CONC FLOOR PER STRC. W/ POLISHED CONC. FINISH	
$\langle 4 \rangle$	2X6 EXTERIOR WALL ASSM.	B-1	WOOD JOIST PER STRC. W/ WOOD FINISH	
5	2X4 & 2X6 INTERIOR WALL ASSM.	(B-2)	WOOD JOIST PER STRC. W/ TILE FINISH	
6	2X6 PLUMBING WALL ASSM.	R-1	WOOD JOIST W/ WOOD DECK PER SPEC.	
$\langle \overline{7} \rangle$	1 HR DBL. 2x4 INTERIOR WALL ASSM.	R-2	WOOD JOIST PER STRC. W/ METAL ROOFING PER SPEC.	
8>	2 HR 2x6 VERTICAL EXIT ENCLOSURE WALL ASSM.			

FLOOR PLAN LEGEND

9 10" CONC. PER STRC.

~ X	FLOOR TYPE
	1 HR
	2 HR
SD	SMOKE DETECTOR
	CARBON MONOXIDE
\bigcirc	EXHAUST (GENERAL NOTES #2,3)
X	WINDOW TAG
XXX	DOOR TAG
×	WALL TYPE
<u> </u>	ELEVATION MARKER
	PROPERTY LINE
> - > -	ACCESSIBLE ROUTE




9 -

(A)-


2' - 6"

_____ -

(E)— –



A3.10



4TH FLOOR 1/4" = 1'-0"

ASSEMBLY TYPES			
WAI	LLS	<u>FLOC</u>	<u>PRS</u>
$\langle 1 \rangle$	12" CONC. PER STRC.	(A-1)	CONC FLOOR PER STRC. W/ WOOD FINISH
2>	8" CMU PER STRC.	(A-2)	CONC FLOOR PER STRC. W/ TILE FINISH
$\langle 3 \rangle$	1HR 2X6 EXTERIOR WALL ASSM.	(A-3)	CONC FLOOR PER STRC. W/ POLISHED CONC. FINISH
4	2X6 EXTERIOR WALL ASSM.	(B-1)	WOOD JOIST PER STRC. W/ WOOD FINISH
5	2X4 & 2X6 INTERIOR WALL ASSM.	B-2>	WOOD JOIST PER STRC. W/ TILE FINISH
6	2X6 PLUMBING WALL ASSM.	R-1	WOOD JOIST W/ WOOD DECK PER SPEC.
$\langle \overline{7} \rangle$	1 HR DBL. 2x4 INTERIOR WALL ASSM.	R-2	WOOD JOIST PER STRC. W/ METAL ROOFING PER SPEC.
8	2 HR 2x6 VERTICAL EXIT		

(**A**)

(B)

(C)

A3.30 1


(E)


_____ _ _ _ _

2 HR 2x6 VERTICAL EXIT ENCLOSURE WALL ASSM. 9 10" CONC. PER STRC.


FLOOR PLAN LEGEND

, - X - °	FLOOR TYPE
	1 HR
	2 HR
SD	SMOKE DETECTOR
	CARBON MONOXIDE
\bigcirc	EXHAUST (GENERAL NOTES #2,3)
X	WINDOW TAG
XXX	DOOR TAG
×	WALL TYPE
	ELEVATION MARKER
	PROPERTY LINE
$\rightarrow - \rightarrow -$	ACCESSIBLE ROUTE






EXISTING FENCE





ELEVATION LEGEND		
	VERTICL STANDING SE	
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	STUCCO	
	2" - BLACK - VERTICAL	
	2X2 - WOOD SIDING	
	PROPERTY LINE (PL)	
	1 HR	
	2 HR	
x	WINDOW TAG	
XXX	DOOR TAG	
X'-X"	ELEVATION MARKER	

DING SEAM ROOF

RTICAL - METAL PANEL










WINDOW TAG DOOR TAG

ELEVATION LEGEND






ELEVATION LEGEND




STANDING SEAM ROOF K - VERTICAL - METAL PANEL NOD SIDING TY LINE (PL) / TAG AG ON MARKER ROOF 41' - 0"	TOB eucalyptus drive, el segundo, ca 90245 [o] 310.322.3700
ROOF 36' - 0"	10/31/19 RENEWAL DATE
LOOR 25' - 9"	2308 PISANI PL VENICE, CA 90291
LOOR 15' - 6"	Revision Schedule Revision Number Revision Date
<u>9 FLOOR</u> 5' - 3"	
<u>G LEVEL</u> 9 13/16" GANI PL. 01 = 0"	
- FL <u>OOR</u> -5' - 0"	ELEVATIONS
	DRAWNCRCHECKEDPNKDATE06/22/2021SCALEAS NOTEDJOB #16080
<u>VATION</u> " = 1'-0"	A3.30




ELEVATION LEGEND		
	VERTICL ST	
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	STUCCO	
	2" - BLACK -	
	2X2 - WOOD	
	PROPERTY	
<u> </u>	1 HR	
	2 HR	
X	WINDOW TA	
XXX	DOOR TAG	
X'-X"	ELEVATION	

PROPOSED SOUTH ELEVA 1/4" =

STANDING SEAM ROOF K - VERTICAL - METAL PANEL DD SIDING TY LINE (PL) TAG G DN MARKER ARIED ROOF ATH FLOOR ATH ATH ATH ATH ATH ATH ATH ATH ATH ATH	CENCLEYAINON
<u>1ST FLOOR</u> -5' - 0"	DRAWN <u>CR</u> CHECKED <u>PNK</u>
/ <u>ATION</u> ' = 1'-0"	DATE



SECTION LEGEND





PROPOSED SECTION A 1/4" = 1'-0" 4

<u>3RD FLOOR</u> 15' - 6"

PARKING L<u>EVEL</u> 1' - 9 13/16" <u>C.L. PIŠANI PL.</u> 100.01 = 0"

<u>1ST FLOOR</u> -5' - 0"





	LANDSCAPE	
TURF AR	EA	
	REA	ļ
TOTAL		ļ

SCAPE	
	0 S.F.
	500 S.F.
	500 S.F.

	HARDSCAPE	
		134 S.F.
-	IMPERVIOUS	4,403 S.F.
	TOTAL	4,537 S.F.

PLANTIN	NG LEG	END						
SYMBOL	QTY.	SIZE	SPACING	BOTANICAL NAME / COMMON NAME	NATIVE	WUCOLS WATER USE TYPES	WATER USE VALUES	HYDRO ZONE
	59	1' - 1.5'	12"	CAREX OSHIMENSIS CVS.	NO	MED	0.5	2
\square	25	N/A	18"- 24" SPREADING	DICHONDRA ARGENTEA	NO	MED	0.5	2
+	2	15'- 25'	N/A	CERCIS SILIQUASTRUM	NO	MED	0.4	2
	6	5'- 15'	5'- 15'	BUXUS SEMPERVIRENS	NO	MED	0.4	2
	14	2'- 3'	1'- 2'	LAVANDULA SPP.	NO	LOW	0.3	1
	3	4'- 6'	2'- 3'	EUCOMIS PALLIDIFLORA SSP. POLE-EVANSII	NO	MED	0.5	2
	14	36" - 48"	24" - 36"	TRADESCANTIA PALLIDA / SPIDERWORT	NO	MED	0.4	2
A.A.A.A.A.A.A.A.A.A.A.A.A.A.A.A.A.A.A.	33	24" - 36"	24" - 36"	ILEX CRENATA / BOX-LEAVED HOLLY	NO	MED	0.4	2
	11	6'- 8'	4'	HYDRANGEA PANICULATA HYBRIDS	NO	MED	0.4	1

CAREX OSHIMENSIS CVS.





EUCOMIS PALLIDIFLORA SSP. POLE-EVANSII TRADESCANTIA PALLIDA / SPIDERWORT



HYDRANGEA PANICULATA HYBRIDS



CERCIS SILIQUASTRUM






BUXUS SEMPERVIRENS



ILEX CRENATA / BOX-LEAVED HOLLY A.





	PROJECT SUMMARY:	NEW 8-UNIT MULTI-FAMILY RESID STORY BUILDING WITH PARKING *UTILIZING INCENTIVES PER LAM
	SCOPE OF WORK:	NEW FOUNDATION, STRUCTURE, CONSTRUCTION (MECHANICAL / PLUMBING) OF NEW 8 UNIT MULT RESIDENCES.
	PROJECT ADDRESS:	2308 PISANI PLACE, VENICE, CA
	NET LOT AREA (AFTER DEDICATIONS):	7,800 S.F.
	ZONE: NUMBER OF STORIES:	R3-1 FOUR (4)
	MAX HEIGHT:	41'-0" W/ VARIED ROOF, 36'-0" FLA
	TOTAL PARKING: TRACT:	12 SPACES VENICE GATEWAY
	BLOCK:	N
	LOT: ASSESSOR PARCEL NUMBER (APN):	14, 15 4237005010
	GROSS LOT AREA:	4237003010 8,000 S.F.
	BUILDABLE LOT AREA:	5,425 S.F.
	RESIDENTIAL S.F.: PARKING S.F.:	11,447 S.F. 2,433 S.F.
	PROJECT TOTAL S.F.:	15,016 S.F.
	NUMBER OF DWELLING UNITS: OPEN SPACE S.F.:	EIGHT (8) 1,615 S.F.
	CONSTRUCTION TYPE:	TYPE V-A
	SPRINKLER:	NFPA-13
1. QU SHOW AND S 2. AL SITE. 3. CC SPEC 4. CC COMI ALL C	TING NOTES JANTITIES GIVEN FOR PLANT MATERIALS S VN FOR CONVENIENCE ONLY AND ARE SU SUPPLY SUFFICIENT NUMBER OF PLANTS L HEADER AND BAMBOO ROOT BARRIERS ONTRACTOR SHALL INSTALL PLANT MATEF FIFICATIONS, DRAWINGS AND DETAILS. ONTRACTOR SHALL PROVIDE A MAINTENAL MENCING AT THE DATE OF FINAL ACCEPT/ CARE PERTAINING TO ALL WORK INSTALLE JMENTS.	BORDINATE TO THE SPAC TO FULFILL SPACING REQ SHALL BE LOCATED BY T RIAL IN ACCORDANCE WIT NCE PERIOD OF NOT LESS ANCE. SUCH MAINTENANC
5. TH DURII 6. TH CON\	HE CONTRACTOR SHALL MAINTAIN A QUAL NG CONSTRUCTION THROUGH COMPLETION HE CONTRACTOR SHALL VERIFY ALL PLAN VENIENCE OF CONTRACTOR. ACTUAL NUM & QUANTITIES DESIGNATED.	ON OF PICK-UP WORK. T MATERIAL QUANTITIES I
diami 8. se Prep	EMOVE ALL DEBRIS, WEEDS, EXCESS MAT ETER FROM PLANTING AREAS PRIOR TO F EE DETAILS AND SPECIFICATIONS FOR ST ARATION, AND BACKFILL REQUIREMENTS LL PLANT MATERIALS SHALL BE APPROVEI	PREPARATION & AGAIN PR AKING METHOD, PLANT PI
INSTA 10. F	ALLATION.	
11. C		
••••	CONTRACTOR SHALL NOTIFY LANDSCAPE	PROJECT OBSERVATION S
	MENCEMENT OF WORK TO COORDINATE F	TINUOUS UNDER ALL TRE
GROU 13. T HEAD AREA FAILU	MENCEMENT OF WORK TO COORDINATE F GROUNDCOVER PLANTING SHALL BE CON JNDCOVER SHALL BE PLANTED ACCORDIN REES SHALL BE LOCATED A MINIMUM OF DERS, AND OTHER TREES WITHIN THE PRO IS AND PLANS, CONTRACTOR TO CONTAC IRE TO MAKE SUCH CONFLICTS KNOWN TO	TINUOUS UNDER ALL TRE NG TO SPACING ON PLANT 5' FROM WALLS, OVERHE DJECT. IF CONFLICTS ARIS T LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHI
GROU 13. T HEAD AREA FAILU IN CC 14. A ORGA OF 10 AMEN	MENCEMENT OF WORK TO COORDINATE F GROUNDCOVER PLANTING SHALL BE CON JNDCOVER SHALL BE PLANTED ACCORDIN REES SHALL BE LOCATED A MINIMUM OF DERS, AND OTHER TREES WITHIN THE PRO IS AND PLANS, CONTRACTOR TO CONTAC	TINUOUS UNDER ALL TRE NG TO SPACING ON PLANT 5' FROM WALLS, OVERHE DJECT. IF CONFLICTS ARIS T LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHI IE MATERIALS. D TO A DEPTH OF 8". APPL ND WITH THE TOP 6" OF S SHALL BE SUPERCEDED F
GROU 13. T HEAD AREA FAILU IN CC 14. A ORGA OF 10 AMEN RECC 15. F USED	MENCEMENT OF WORK TO COORDINATE F GROUNDCOVER PLANTING SHALL BE CON JNDCOVER SHALL BE PLANTED ACCORDIN REES SHALL BE LOCATED A MINIMUM OF DERS, AND OTHER TREES WITHIN THE PRO S AND PLANS, CONTRACTOR TO CONTAC IRE TO MAKE SUCH CONFLICTS KNOWN TO INTRACTORS LIEABILITY TO RELOCATE TH ALL PLANTING AREAS SHALL BE LOOSENED ANIC AMENDMENT AND 15 LBS. D-10-10 FERTILIZER PER 1000 S.F. AND BLEI DIMENT IS FOR BIDDING PURPOSES, AND DMMENDATIONS OF THE SOIL ANALYSIS RI FOR ALL TREES AND SHURB PLANTING, TH D FOR BACKFILL IN THE PLANTERS. THIS M ERCEDED BY RECOMMENDATIONS OF THE SITE SOIL - 6 PARTS BY VOLUME ORGANIC AMENDMENT - 4 PARTS BY VO SOIL CONDITIONER / FERTILIZER 10-10-	TINUOUS UNDER ALL TRE NG TO SPACING ON PLANT 5' FROM WALLS, OVERHE, DJECT. IF CONFLICTS ARIS T LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHI IE MATERIALS. D TO A DEPTH OF 8". APPL ND WITH THE TOP 6" OF S SHALL BE SUPERCEDED F EPORT. IE FOLLOWING PREPAREI IX IS FOR BIDDING PURPO SOIL ANALYSIS REPORT.
GROU 13. T HEAD AREA FAILU IN CC 14. A ORGA OF 10 AMEN RECC 15. F USED SUPE 16. TU IS AD	MENCEMENT OF WORK TO COORDINATE F GROUNDCOVER PLANTING SHALL BE CON JNDCOVER SHALL BE PLANTED ACCORDIN REES SHALL BE LOCATED A MINIMUM OF DERS, AND OTHER TREES WITHIN THE PRO S AND PLANS, CONTRACTOR TO CONTAC IRE TO MAKE SUCH CONFLICTS KNOWN TO INTRACTORS LIEABILITY TO RELOCATE TH ALL PLANTING AREAS SHALL BE LOOSENED ANIC AMENDMENT AND 15 LBS. D-10-10 FERTILIZER PER 1000 S.F. AND BLEI NDMENT IS FOR BIDDING PURPOSES, AND DMMENDATIONS OF THE SOIL ANALYSIS RI FOR ALL TREES AND SHURB PLANTING, TH D FOR BACKFILL IN THE PLANTERS. THIS M RCEDED BY RECOMMENDATIONS OF THE SITE SOIL - 6 PARTS BY VOLUME ORGANIC AMENDMENT - 4 PARTS BY VOL	TINUOUS UNDER ALL TRENG TO SPACING ON PLANT 5' FROM WALLS, OVERHEAD DJECT. IF CONFLICTS ARIS T LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHI IE MATERIALS. D TO A DEPTH OF 8". APPL ND WITH THE TOP 6" OF S SHALL BE SUPERCEDED F EPORT. IE FOLLOWING PREPAREI IX IS FOR BIDDING PURPO SOIL ANALYSIS REPORT. DLUME 10-1LB. PER C.Y. OF MIX ER THAN 25% WHERE THE PE
GROU 13. T HEAD AREA FAILU IN CC 14. A ORGA OF 10 AMEN RECO 15. F USED SUPE 16. TU IS AD 17. RE 18. A SURF	MENCEMENT OF WORK TO COORDINATE F GROUNDCOVER PLANTING SHALL BE CON JNDCOVER SHALL BE PLANTED ACCORDIN REES SHALL BE LOCATED A MINIMUM OF DERS, AND OTHER TREES WITHIN THE PRO S AND PLANS, CONTRACTOR TO CONTAC IRE TO MAKE SUCH CONFLICTS KNOWN TO INTRACTORS LIEABILITY TO RELOCATE TH ALL PLANTING AREAS SHALL BE LOOSENED ANIC AMENDMENT AND 15 LBS. D-10-10 FERTILIZER PER 1000 S.F. AND BLEI NDMENT IS FOR BIDDING PURPOSES, AND DMMENDATIONS OF THE SOIL ANALYSIS RI FOR ALL TREES AND SHURB PLANTING, TH D FOR BACKFILL IN THE PLANTERS. THIS M IRCEDED BY RECOMMENDATIONS OF THE SITE SOIL - 6 PARTS BY VOLUME ORGANIC AMENDMENT - 4 PARTS BY VOL SOIL CONDITIONER / FERTILIZER 10-10-7 IRON SULFATE - 2 LBS. PER C.Y.OF MIX	TINUOUS UNDER ALL TRENG TO SPACING ON PLANT 5' FROM WALLS, OVERHEAD DJECT. IF CONFLICTS ARIS T LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHI IE MATERIALS. D TO A DEPTH OF 8". APPL ND WITH THE TOP 6" OF S SHALL BE SUPERCEDED F EPORT. IE FOLLOWING PREPAREI IX IS FOR BIDDING PURPO SOIL ANALYSIS REPORT. DLUME 10-1LB. PER C.Y. OF MIX ER THAN 25% WHERE THE PE E USED FOR WATER FEAT BE APPLIED ON ALL EXPO
GROU 13. T HEAD AREA FAILU IN CC 14. A ORGA OF 10 AMEN RECC 15. F USED SUPE 16. TU IS AD 17. RE 18. A SURF GROU 19. FO RATE	MENCEMENT OF WORK TO COORDINATE F GROUNDCOVER PLANTING SHALL BE CON JNDCOVER SHALL BE PLANTED ACCORDIN REES SHALL BE LOCATED A MINIMUM OF DERS, AND OTHER TREES WITHIN THE PRO S AND PLANS, CONTRACTOR TO CONTAC INE TO MAKE SUCH CONFLICTS KNOWN TO INTRACTORS LIEABILITY TO RELOCATE TH ALL PLANTING AREAS SHALL BE LOOSENED ANIC AMENDMENT AND 15 LBS. D-10-10 FERTILIZER PER 1000 S.F. AND BLEI ANIC AMENDMENT AND 15 LBS. D-10-10 FERTILIZER PER 1000 S.F. AND BLEI IDMENT IS FOR BIDDING PURPOSES, AND DMMENDATIONS OF THE SOIL ANALYSIS RI FOR ALL TREES AND SHURB PLANTING, TH D FOR BACKFILL IN THE PLANTERS. THIS M RECEDED BY RECOMMENDATIONS OF THE SITE SOIL - 6 PARTS BY VOLUME ORGANIC AMENDMENT - 4 PARTS BY VO SOIL CONDITIONER / FERTILIZER 10-10-1 IRON SULFATE - 2 LBS. PER C.Y.OF MIX JRF IS NOT ALLOWED ON SLOPES GREATE DJACENT TO AN IMPERMEABLE HARDSCAF ECIRCULATING WATER SYSTEMS SHALL B MINIMUM 3-INCH LAYER OF MULCH SHALL FACES OF PLANTING AREAS EXCEPT TURF	TINUOUS UNDER ALL TRENG TO SPACING ON PLANT 5' FROM WALLS, OVERHEADJECT. IF CONFLICTS ARIS T LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHI IE MATERIALS. D TO A DEPTH OF 8". APPL ND WITH THE TOP 6" OF S SHALL BE SUPERCEDED B EPORT. IE FOLLOWING PREPAREI IX IS FOR BIDDING PURPO SOIL ANALYSIS REPORT. DLUME 10-1LB. PER C.Y. OF MIX ER THAN 25% WHERE THE PE E USED FOR WATER FEAT BE APPLIED ON ALL EXPO AREAS, CREEPING OR RO TIONS WHERE MULCH IS R IN THE TOP 6 INCHES OF ER 1,000 SQUARE FEET OF
GROU 13. T HEAD AREA FAILU IN CC 14. A ORGA OF 10 AMEN RECC 15. F USED SUPE 16. TU IS AD 17. RE 18. A SURF GROU 19. FC RATE SHAL 20. I A ORDII COME	MENCEMENT OF WORK TO COORDINATE F GROUNDCOVER PLANTING SHALL BE CON JNDCOVER SHALL BE PLANTED ACCORDIN REES SHALL BE LOCATED A MINIMUM OF DERS, AND OTHER TREES WITHIN THE PRO S AND PLANS, CONTRACTOR TO CONTAC INE TO MAKE SUCH CONFLICTS KNOWN TO DITRACTORS LIEABILITY TO RELOCATE TH ALL PLANTING AREAS SHALL BE LOOSENED ANIC AMENDMENT AND 15 LBS. 0-10-10 FERTILIZER PER 1000 S.F. AND BLED JDMENT IS FOR BIDDING PURPOSES, AND DMMENDATIONS OF THE SOIL ANALYSIS RI FOR ALL TREES AND SHURB PLANTING, TH D FOR BACKFILL IN THE PLANTERS. THIS M RCEDED BY RECOMMENDATIONS OF THE SITE SOIL - 6 PARTS BY VOLUME ORGANIC AMENDMENT - 4 PARTS BY VOLUME ON SULFATE - 2 LBS. PER C.Y.OF MIX JJRF IS NOT ALLOWED ON SLOPES GREATE DJACENT TO AN IMPERMEABLE HARDSCAP ECIRCULATING WATER SYSTEMS SHALL B MINIMUM 3-INCH LAYER OF MULCH SHALL FACES OF PLANTING AREAS EXCEPT TURF JNDCOVER, OR DIRECT SEEDING APPLICA OF A MINIMUM OF FOUR CUBIC YARDS PE L BE INCORPORATED TO A DEPTH OF SIX AGREE TO COMPLY WITH THE REQUIREME NANCE AND SUBMIT A COMPLETE LANDSO PLYS WITH THE PERFORMANCE APPROAC	TINUOUS UNDER ALL TRENG TO SPACING ON PLANT 5' FROM WALLS, OVERHED DJECT. IF CONFLICTS ARIS T LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHI IE MATERIALS. D TO A DEPTH OF 8". APPL ND WITH THE TOP 6" OF S SHALL BE SUPERCEDED F EPORT. IE FOLLOWING PREPAREI IX IS FOR BIDDING PURPO SOIL ANALYSIS REPORT. DLUME 10-1LB. PER C.Y. OF MIX ER THAN 25% WHERE THE PE E USED FOR WATER FEAT BE APPLIED ON ALL EXPO AREAS, CREEPING OR RO TIONS WHERE MULCH IS R IN THE TOP 6 INCHES OI ER 1,000 SQUARE FEET OF INCHES INTO THE SOIL.
GROU 13. T HEAD AREA FAILU IN CC 14. A ORGA OF 10 AMEN RECC 15. F USED SUPE 16. TU IS AD 17. RE 18. A SURF GROU 19. FC RATE SHAL 20. I A ORDII COMF DATE 21. AT OF TH IRRIG IRRIG	MENCEMENT OF WORK TO COORDINATE F GROUNDCOVER PLANTING SHALL BE CON- JNDCOVER SHALL BE PLANTED ACCORDIN REES SHALL BE LOCATED A MINIMUM OF DERS, AND OTHER TREES WITHIN THE PRO- S AND PLANS, CONTRACTOR TO CONTAC IRE TO MAKE SUCH CONFLICTS KNOWN TO INTRACTORS LIEABILITY TO RELOCATE TH ALL PLANTING AREAS SHALL BE LOOSENED ANIC AMENDMENT AND 15 LBS. -10-10 FERTILIZER PER 1000 S.F. AND BLEI JDMENT IS FOR BIDDING PURPOSES, AND DMMENDATIONS OF THE SOIL ANALYSIS RI FOR ALL TREES AND SHURB PLANTING, TH D FOR BACKFILL IN THE PLANTERS. THIS M RCEDED BY RECOMMENDATIONS OF THE SITE SOIL - 6 PARTS BY VOLUME ORGANIC AMENDMENT - 4 PARTS BY VOL SOIL CONDITIONER / FERTILIZER 10-10- IRON SULFATE - 2 LBS. PER C.Y.OF MIX JRF IS NOT ALLOWED ON SLOPES GREATE DACENT TO AN IMPERMEABLE HARDSCAF ECIRCULATING WATER SYSTEMS SHALL B MINIMUM 3-INCH LAYER OF MULCH SHALL ACES OF PLANTING AREAS EXCEPT TURF JNDCOVER, OR DIRECT SEEDING APPLICA OR SOILS LESS THAN 6% ORGANIC MATTE OF A MINIMUM OF FOUR CUBIC YARDS PE L BE INCORPORATED TO A DEPTH OF SIX AGREE TO COMPLY WITH THE REQUIREME NANCE AND SUBMIT A COMPLETE LANDSO PLYS WITH THE PERFORMANCE APPROAC SOLYS WITH THE PERFORMANCE APPROAC AND SUBMIT A COMPLETE LANDSO PLYS WITH THE PERFORMANCE APPROAC ATION SCHEDULE AND SCHEDULE OF LAN	TINUOUS UNDER ALL TRENG TO SPACING ON PLANT 5' FROM WALLS, OVERHEL DJECT. IF CONFLICTS ARIS T LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITE IE MATERIALS. D TO A DEPTH OF 8". APPL ND WITH THE TOP 6" OF S SHALL BE SUPERCEDED F EPORT. IE FOLLOWING PREPAREI IX IS FOR BIDDING PURPO SOIL ANALYSIS REPORT. DLUME 10-1LB. PER C.Y. OF MIX ER THAN 25% WHERE THE PE E USED FOR WATER FEAT BE APPLIED ON ALL EXPO AREAS, CREEPING OR RO TIONS WHERE MULCH IS R IN THE TOP 6 INCHES OF FR 1,000 SQUARE FEET OF INCHES INTO THE SOIL. ENTS OF THE WATER EFFIC CAPE DOCUMENTATION PA H. SIGNED
GROU 13. T HEAD AREA FAILU IN CO 14. A ORGA OF 10 AMEN RECO 15. F USED SUPE 16. TU IS AD 17. RE 18. A SURF GROU 19. FO RATE SHAL 20. I A ORDI COME DATE 21. AT OR THIR IRRIG I. CO REPA CONS AND F 2. AL	MENCEMENT OF WORK TO COORDINATE F GROUNDCOVER PLANTING SHALL BE CON- JNDCOVER SHALL BE PLANTED ACCORDIN TREES SHALL BE LOCATED A MINIMUM OF DERS, AND OTHER TREES WITHIN THE PRO- S AND PLANS, CONTRACTOR TO CONTAC JRE TO MAKE SUCH CONFLICTS KNOWN TO DATACTORS LIEABILITY TO RELOCATE TH ALL PLANTING AREAS SHALL BE LOOSENEL ANIC AMENDMENT AND 15 LBS. -10-10 FERTILIZER PER 1000 S.F. AND BLEI JDMENT IS FOR BIDDING PURPOSES, AND DMMENDATIONS OF THE SOIL ANALYSIS RI TOR ALL TREES AND SHURB PLANTING, TH D FOR BACKFILL IN THE PLANTERS. THIS M RCEDED BY RECOMMENDATIONS OF THE SITE SOIL - 6 PARTS BY VOLUME ORGANIC AMENDMENT - 4 PARTS BY VOLONE IRON SULFATE - 2 LBS. PER C.Y.OF MIX JRF IS NOT ALLOWED ON SLOPES GREATE DJACENT TO AN IMPERMEABLE HARDSCAF ECIRCULATING WATER SYSTEMS SHALL B MINIMUM 3-INCH LAYER OF MULCH SHALL ACES OF PLANTING AREAS EXCEPT TURF JNDCOVER, OR DIRECT SEEDING APPLICA DR SOILS LESS THAN 6% ORGANIC MATTE OF A MINIMUM OF FOUR CUBIC YARDS PE L BE INCORPORATED TO A DEPTH OF SIX AGREE TO COMPLY WITH THE REQUIREME NANCE AND SUBMIT A COMPLETE LANDSC PLYS WITH THE PERFORMANCE APPROAC COMPLY WITH THE PERFORMANCE APPROAC THE TIME OF FINAL INSPECTION THE PERF HE PROPERTY WITH A CERTIFICATE OF COMPLY ATION SCHEDULE AND SCHEDULE OF LANDSC PLYS WITH THE PERFORMANCE APPROAC	TINUOUS UNDER ALL TRENG TO SPACING ON PLANT 5' FROM WALLS, OVERHED DJECT. IF CONFLICTS ARIS T LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITE IE MATERIALS. D TO A DEPTH OF 8". APPL ND WITH THE TOP 6" OF S SHALL BE SUPERCEDED F EPORT. IE FOLLOWING PREPAREIT IX IS FOR BIDDING PURPO SOIL ANALYSIS REPORT. DLUME 10-1LB. PER C.Y. OF MIX ER THAN 25% WHERE THE PE E USED FOR WATER FEAT BE APPLIED ON ALL EXPORT AREAS, CREEPING OR RO TIONS WHERE MULCH IS R IN THE TOP 6 INCHES OF F 1,000 SQUARE FEET OF INCHES INTO THE SOIL. SITS OF THE WATER EFFIC CAPE DOCUMENTATION PA H. DIGNED RIT APPLICANT MUST PR DMPLETION, CERTIFICATE NDSCAPE AND IRRIGATION RIGATION SYSTEM. CONTI PE AND IRRIGATION DAMAG APE CONDITION WITH A F CONTAINED CONDITIONS. UP STREAM BUBBLERS, M
GROU 13. T HEAD AREA FAILU IN CO 14. A ORGA OF 10 AMEN RECO 15. F USED SUPE 16. TU IS AD 17. RE 18. A SURF GROU 19. FO RATE SHAL 20. I A ORDIE COMF DATE 21. AT ORDIE COMF 1. CO RATE SHAL 20. I A ORDIE COMF DATE SHAL 20. I A ORDIE COMF DATE SHAL 20. I A ORDIE COMF DATE SHAL 20. I A ORDIE COMF DATE SHAL 20. I A ORDIE COMF AND I SHAL 20. I A A A A A A A A A A A A A A	MENCEMENT OF WORK TO COORDINATE F GROUNDCOVER PLANTING SHALL BE CON JNDCOVER SHALL BE PLANTED ACCORDIN TREES SHALL BE LOCATED A MINIMUM OF DERS, AND OTHER TREES WITHIN THE PRO S AND PLANS, CONTRACTOR TO CONTAC IRE TO MAKE SUCH CONFLICTS KNOWN TO INTRACTORS LIEABILITY TO RELOCATE TH ALL PLANTING AREAS SHALL BE LOOSENED ANIC AMENDMENT AND 15 LBS. -10-10 FERTILIZER PER 1000 S.F. AND BLEI IDMENT IS FOR BIDDING PURPOSES, AND DMMENDATIONS OF THE SOIL ANALYSIS RI FOR ALL TREES AND SHURB PLANTING, TH D FOR BACKFILL IN THE PLANTERS. THIS M RCEDED BY RECOMMENDATIONS OF THE SITE SOIL - 6 PARTS BY VOLUME ORGANIC AMENDMENT - 4 PARTS BY VO SOIL CONDITIONER / FERTILIZER 10-10- IRON SULFATE - 2 LBS. PER C.Y.OF MIX JRF IS NOT ALLOWED ON SLOPES GREATE DJACENT TO AN IMPERMEABLE HARDSCAF ECIRCULATING WATER SYSTEMS SHALL B MINIMUM 3-INCH LAYER OF MULCH SHALL ACES OF PLANTING AREAS EXCEPT TURF JNDCOVER, OR DIRECT SEEDING APPLICA OR SOILS LESS THAN 6% ORGANIC MATTE OF A MINIMUM OF FOUR CUBIC YARDS PE L BE INCORPORATED TO A DEPTH OF SIX AGREE TO COMPLY WITH THE REQUIREMEN NANCE AND SUBMIT A COMPLETE LANDSC PLYS WITH THE PERFORMANCE APPROAC ATION NOTES THE TIME OF FINAL INSPECTION THE PEF HE PROPERTY WITH A CERTIFICATE OF CO ATION SCHEDULE AND SCHEDULE OF LAN STRAUCTION TO AN ACCEPTABLE LANDSC PLYS WITH THE PERFORMANCE APPROAC ATION NOTES INTRACTOR IS TO AUGMENT EXISTING IRI IR OR REPLACE ANY EXISTING LANDSCAP STRAUCTION TO AN ACCEPTABLE LANDSC PERFICIENT IRRIGATION SYSTEM PER THE C ATION NOTES	TINUOUS UNDER ALL TRENG TO SPACING ON PLANT 5' FROM WALLS, OVERHE, DJECT. IF CONFLICTS ARIS T LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT IS NOT A DEPTH OF 8". APPL ND WITH THE TOP 6" OF S SHALL BE SUPERCEDED FOR SOIL ANALYSIS REPORT. DUME 10-1LB. PER C.Y. OF MIX ER THAN 25% WHERE THE PE E USED FOR WATER FEAT BE APPLIED ON ALL EXPORT AREAS, CREEPING OR RO TIONS WHERE MULCH IS R IN THE TOP 6 INCHES OF R 1,000 SQUARE FEET OF INCHES INTO THE SOIL. ENTS OF THE WATER EFFIC CAPE DOCUMENTATION PA H. SIGNED RIT APPLICANT MUST PR OMPLETION, CERTIFICATE NDSCAPE AND IRRIGATION RIGATION SYSTEM. CONTI PAD IRRIGATION DAMAG APE CONDITION WITH A F CONTAINED CONDITIONS. UP STREAM BUBBLERS, M E ON A SEPARATE VALVE. P-UPS: 6" FOR LAWN, LOW UB AREAS. HEADS ON RIS
GROU 13. T HEAD AREA FAILU IN CO 14. A ORGA OF 10 AMEN RECO 15. F USED SUPE 16. TU IS AL 17. RE 18. A SURF GROU 19. FO RATE SHAL 20. I A ORDII COMF DATE SHAL 20. I A ORDII COMF DATE SHAL 20. I A ORDII COMF DATE SHAL 20. I A ORDII COMF DATE SHAL 20. I A ORDII COMF DATE SHAL 20. I A ORDII COMF DATE SHAL 20. I A ORDII COMF AND I 2. AL WITH 3. SF PARK ALLO 4. LO	MENCEMENT OF WORK TO COORDINATE F GROUNDCOVER PLANTING SHALL BE CON JNDCOVER SHALL BE PLANTED ACCORDIN TREES SHALL BE LOCATED A MINIMUM OF TRESS SHALL BE LOCATED A MINIMUM OF PERS, AND OTHER TREES WITHIN THE PRO S, AND PLANS, CONTRACTOR TO CONTAC INTRACTORS LIEABILITY TO RELOCATE TH ALL PLANTING AREAS SHALL BE LOOSENEI ANIC AMENDMENT AND 15 LBS. 10-10 FERTILIZER PER 1000 S.F. AND BLEI DIMENT IS FOR BIDDING PURPOSES, AND DOMMENDATIONS OF THE SOIL ANALYSIS RI FOR ALL TREES AND SHURB PLANTING, TH 0 FOR BACKFILL IN THE PLANTERS. THIS M 10 FOR BACKFILL IN THE PLANTERS. 10 FI S NOT ALLOWED ON SLOPES GREATE 10 FOR BACKFILL IN THE PLANTERS. 10 FI S NOT ALLOWED ON SLOPES GREATE 10 FOR SOILS LESS THAN 6% ORGANIC MATTE 10 F A MINIMUM OF FOUR CUBIC YARDS PE 10 BE INCORPORATED TO A DEPTH OF SIX 10 F SOILS LESS THAN 6% ORGANIC MATTE 10 F A MINIMUM OF FOUR CUBIC YARDS PE 11 BE INCORPORATED TO A DEPTH OF SIX 10 F SOILS LESS THAN 6% ORGANIC MATTE 10 F A MINIMUM OF FOUR CUBIC YARDS PE 11 THE TIME OF FINAL INSPECTION THE PEFF 12 PROPERTY WITH A CERTIFICATE OF COMPLEX 13 THE TIME OF FINAL INSPECTION THE PEFF 14 PROPERTY WITH A CERTIFICATE OF COMPLEX 14 OF TREE. TREE IRRIGATION SHALL BE 15 THE TIME OF FINAL INSPECTION THE PEFF 16 PROPERTY WITH A CERTIFICATE OF SHRING 16 CAR OVERHANG AREAS, 12" FOR SHRING 17 THE TI	TINUOUS UNDER ALL TRENG TO SPACING ON PLANT 5' FROM WALLS, OVERHEADJECT. IF CONFLICTS ARIS T LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O TO A DEPTH OF 8". APPL ND WITH THE TOP 6" OF S SHALL BE SUPERCEDED F EPORT. IE FOLLOWING PREPAREIT IX IS FOR BIDDING PURPO SOIL ANALYSIS REPORT. OLUME 10-1LB. PER C.Y. OF MIX ER THAN 25% WHERE THE PE E USED FOR WATER FEAT BE APPLIED ON ALL EXPOR AREAS, CREEPING OR RO TIONS WHERE MULCH IS R IN THE TOP 6 INCHES OF R 1,000 SQUARE FEET OF INCHES INTO THE SOIL. CAREAS, CREEPING OR RO CAPE DOCUMENTATION P/ H. GONED RIT APPLICANT MUST PR DMPLETION, CERTIFICATE NDSCAPE AND IRRIGATION RIGATION SYSTEM. CONTI PAND IRRIGATION DAMAG APE CONDITION WITH A F CONTAINED CONDITIONS. UP STREAM BUBBLERS, M E ON A SEPARATE VALVE. P-UPS: 6" FOR LAWN, LOW UB AREAS. HEADS ON RIS SPACE FOR POP-UPS.
GROU 13. T HEAD AREA FAILU 14. A ORGA OF 10 AMEN 15. F USED 16. TU IS AD 17. RE 18. A SUPE 16. TU IS AD 17. RE 18. A SUPE 19. FC SHAL 20. I A ORDIT DATE 21. AT ORDIT COME 1. CO RATES SHAL 20. I A ORDIT DATE 21. AT ORDIT COME AND T IRRIG 2. AL WITH 3. SE PARKA ALLO 15. CO SIRRIG	MENCEMENT OF WORK TO COORDINATE F GROUNDCOVER PLANTING SHALL BE CON JNDCOVER SHALL BE PLANTED ACCORDIN TREES SHALL BE LOCATED A MINIMUM OF TRESS SHALL BE LOCATED A MINIMUM OF PERS, AND OTHER TREES WITHIN THE PRO S, AND PLANS, CONTRACTOR TO CONTAC INTRACTORS LIEABILITY TO RELOCATE TH ALL PLANTING AREAS SHALL BE LOOSENEI ANIC AMENDMENT AND 15 LBS. 10-10 FERTILIZER PER 1000 S.F. AND BLEI DIMENT IS FOR BIDDING PURPOSES, AND DOMMENDATIONS OF THE SOIL ANALYSIS RI FOR ALL TREES AND SHURB PLANTING, TH 0 FOR BACKFILL IN THE PLANTERS. THIS M 10 FOR BACKFILL IN THE PLANTERS. 10 FI S NOT ALLOWED ON SLOPES GREATE 10 FOR BACKFILL IN THE PLANTERS. 10 FI S NOT ALLOWED ON SLOPES GREATE 10 FOR SOILS LESS THAN 6% ORGANIC MATTE 10 F A MINIMUM OF FOUR CUBIC YARDS PE 10 BE INCORPORATED TO A DEPTH OF SIX 10 F SOILS LESS THAN 6% ORGANIC MATTE 10 F A MINIMUM OF FOUR CUBIC YARDS PE 11 BE INCORPORATED TO A DEPTH OF SIX 10 F SOILS LESS THAN 6% ORGANIC MATTE 10 F A MINIMUM OF FOUR CUBIC YARDS PE 11 THE TIME OF FINAL INSPECTION THE PEFF 12 PROPERTY WITH A CERTIFICATE OF COMPLEX 13 THE TIME OF FINAL INSPECTION THE PEFF 14 PROPERTY WITH A CERTIFICATE OF COMPLEX 14 OF TREE. TREE IRRIGATION SHALL BE 15 THE TIME OF FINAL INSPECTION THE PEFF 16 PROPERTY WITH A CERTIFICATE OF SHRING 16 CAR OVERHANG AREAS, 12" FOR SHRING 17 THE TI	TINUOUS UNDER ALL TRENG TO SPACING ON PLANT 5' FROM WALLS, OVERHEL DJECT. IF CONFLICTS ARIS T LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O TO A DEPTH OF 8". APPL ND WITH THE TOP 6" OF S SHALL BE SUPERCEDED F EPORT. IE FOLLOWING PREPAREIT IX IS FOR BIDDING PURPO SOIL ANALYSIS REPORT. OLUME 10-1LB. PER C.Y. OF MIX ER THAN 25% WHERE THE PE E USED FOR WATER FEAT BE APPLIED ON ALL EXPORT AREAS, CREEPING OR RO TIONS WHERE MULCH IS R IN THE TOP 6 INCHES OF FR 1,000 SQUARE FEET OF INCHES INTO THE SOIL. ENTS OF THE WATER EFFIC CAPE DOCUMENTATION P/ H. GONED RINT APPLICANT MUST PR OMPLETION, CERTIFICATE NDSCAPE AND IRRIGATION RIGATION SYSTEM. CONTI PE AND IRRIGATION WITH A F CONTAINED CONDITIONS. UP STREAM BUBBLERS, M E ON A SEPARATE VALVE. P-UPS: 6" FOR LAWN, LOW UB AREAS. HEADS ON RIS SPACE FOR POP-UPS. //OUS PAVING TO PREVEN SPACE FOR POP-UPS.
GROU 13. THEADA FAILUI 14. AC OF 10 14. AC OF 10 14. AC OF 10 15. FUSED 15. FUSED 16. TU 15. FUSED 16. TU 17. RE 18. A SURF GROU 19. FC SHAL 20. LA ORDHI COMH 21. AT ORDHI 21. AT 21. AT	MENCEMENT OF WORK TO COORDINATE F SROUNDCOVER PLANTING SHALL BE CON JNDCOVER SHALL BE PLANTED ACCORDIN REES SHALL BE LOCATED A MINIMUM OF JERS, AND OTHER TREES WITHIN THE PRO S AND PLANS, CONTRACTOR TO CONTAC IRE TO MAKE SUCH CONFLICTS KNOWN TH INTRACTORS LIEABILITY TO RELOCATE TH ALL PLANTING AREAS SHALL BE LOOSENEL ANIC AMENDMENT AND 15 LBS. JOL-10 FERTILIZER PER 1000 S.F. AND BLEI JOMENT IS FOR BIDDING PURPOSES, AND DMMENDATIONS OF THE SOIL ANALYSIS RI COR ALL TREES AND SHURB PLANTING, TH POR BACKFILL IN THE PLANTERS. THIS M RECEDED BY RECOMMENDATIONS OF THE SITE SOIL - 6 PARTS BY VOLUME ORGANIC AMENDMENT - 4 PARTS BY VO SOIL CONDITIONER / FERTILIZER 10-10- IRON SULFATE - 2 LBS. PER C.Y.OF MIX JRF IS NOT ALLOWED ON SLOPES GREATE DACENT TO AN IMPERMEABLE HARDSCAF ECIRCULATING WATER SYSTEMS SHALL B MINIMUM 3-INCH LAYER OF MULCH SHALL ACES OF PLANTING AREAS EXCEPT TURF JNDCOVER, OR DIRECT SEEDING APPLICA OR SOILS LESS THAN 6% ORGANIC MATTE OF A MINIMUM OF FOUR CUBIC YARDS PP L BE INCORPORATED TO A DEPTH OF SIX GREET O COMPLY WITH THE REQUIREME NANCE AND SUBMIT A COMPLETE LANDSC PLYS WITH THE PERFORMANCE APPROAC PLYS WITH THE PERFORMANCE APPROAC SPLYS WITH THE PERFORMANCE APPROAC SPLYS WITH THE PERFORMANCE APPROAC PLYS WITH THE PERFORMANCE APPROAC STR4UCTION TO AN ACCEPTABLE LANDSC PLYS WITH THE PERFORMANCE APPROAC STR4UCTION TO AN ACCEPTABLE LANDSC PLYS WITH THE PERFORMANCE APPROAC STR4UCTION TO AN ACCEPTABLE LANDSC SPLYS WITH THE PERFORMANCE APPROAC STR4UCTION TO AN ACCEPTABLE LANDSC SFLICIENT IRRIGATION SYSTEM PER THE C L NEW TREES REQUIRE INDIVIDUAL POP-I IN 4' OF TREE. TREE IRRIGATION SHALL BE PRAY OR ROTOR HEADS SHALL BE ON POI ED CAR OVERHANG AREAS, 12" FOR SHRI WED ADJACENT TO WALLS WITH LIMITED DATRACTOR SHALL REPLACE ANY EXISTING SENSOR TO PROVIDE WEATHER BASED IN AATION RUNTIMES BASED ON WEATHER. S GER OR EQUIVALENT. E PLANTING AND IRRIGATION SYSTEM SHALL LOPER/BUILDER PRIOR TO THE CLOSE OF PROJECT OR PHASE.	TINUOUS UNDER ALL TRENG TO SPACING ON PLANT 5' FROM WALLS, OVERHE, DJECT. IF CONFLICTS ARIS T LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHI IE MATERIALS. D TO A DEPTH OF 8". APPL ND WITH THE TOP 6" OF S SHALL BE SUPERCEDED IN EPORT. IE FOLLOWING PREPAREI IX IS FOR BIDDING PURPOR SOIL ANALYSIS REPORT. DLUME 10-1LB. PER C.Y. OF MIX ER THAN 25% WHERE THE PE E USED FOR WATER FEAT BE APPLIED ON ALL EXPO AREAS, CREEPING OR RO TIONS WHERE MULCH IS R IN THE TOP 6 INCHES ON ER 1,000 SQUARE FEET OF INCHES INTO THE SOIL. CAPE DOCUMENTATION P/ H. IGNED RINT APPLICANT MUST PR DMPLETION, CERTIFICATE NDSCAPE AND IRRIGATION RIGATION SYSTEM. CONTI PE AND IRRIGATION DAMAGE APE CONDITIONS. UP STREAM BUBBLERS, M E ON A SEPARATE VALVE. P-UPS: 6" FOR LAWN, LOW UB AREAS. HEADS ON RIS SPACE FOR POP-UPS. //OUS PAVING TO PREVENS SPACE FOR POP-UPS. //OUS PAVING TO PREVENS RIGATION CONTROLL FORMATION THAT WILL AU EE HUNTER SOLAR SYNC
GROU 13. T HEAD AREA FAILU 14. A ORGA OF 10 AMEN 15. F USED 16. TU IS AD 17. RE 18. A SUPE 16. TU IS AD 17. RE 18. A SUPE 10. I A ORDE COME 19. FC SUPE 10. I A ORDE COME 19. FC SUPE 10. I A ORDE COME 1. CO RATE 20. I A ORDE COME 1. CO RATE 2. AL ORDE COME 1. CO RATE COME 1. CO RATE COME 1. CO RATE COME 1. CO RATE COME 1. CO RATE COME 1. CO RATE COME 1. CO RATE COM	MENCEMENT OF WORK TO COORDINATE F SROUNDCOVER PLANTING SHALL BE CON JNDCOVER SHALL BE PLANTED ACCORDIN REES SHALL BE LOCATED A MINIMUM OF DERS, AND OTHER TREES WITHIN THE PRO S AND PLANS, CONTRACTOR TO CONTAC INTRACTORS LIEABILITY TO RELOCATE TH ALL PLANTING AREAS SHALL BE LOOSENEL NIC AMENDMENT AND 15 LBS. (+10-10 FERTILIZER PER 1000 S.F. AND BLEI JOMENT IS FOR BIDDING PURPOSES, AND JMMENDATIONS OF THE SOIL ANALYSIS RI COR ALL TREES AND SHURB PLANTING, TH POR BACKFILL IN THE PLANTERS. THIS M RCEDED BY RECOMMENDATIONS OF THE SITE SOIL - 6 PARTS BY VOLUME ORGANIC AMENDMENT - 4 PARTS BY VC SOIL CONDITIONER / FERTILIZER 10-10- IRON SULFATE - 2 LBS. PER C.Y.OF MIX JRF IS NOT ALLOWED ON SLOPES GREATE DACENT TO AN IMPERMEABLE HARDSCAF ECIRCULATING WATER SYSTEMS SHALL B MINIMUM 3-INCH LAYER OF MULCH SHALL ACES OF PLANTING AREAS EXCEPT TURF JNDCOVER, OR DIRECT SEEDING APPLICA OR SOILS LESS THAN 6% ORGANIC MATTE OF A MINIMUM OF FOUR CUBIC YARDS PE L BE INCORPORATED TO A DEPTH OF SIX AGREE TO COMPLY WITH THE REQUIREME NANCE AND SUBMIT A COMPLETE LANDSC PLYS WITH THE PERFORMANCE APPROAC CONSULS LESS THAN 6% ORGANIC MATTE OF A MINIMUM OF FOUR CUBIC YARDS PE L BE INCORPORATED TO A DEPTH OF SIX AGREE TO COMPLY WITH A CERTIFICATE OF CO ATION SCHEDULE AND SCHEDULE OF LAN STATUON THE PERFORMANCE APPROAC CONTRACTOR IS TO AUGMENT EXISTING IRI IR OR REPLACE ANY EXISTING LANDSCAP STRAUCTION TO AN ACCEPTABLE LANDSC PLYS WITH THE PERFORMANCE APPROAC CHT TREES REQUIRE INDIVIDUAL POP-I IN 4' OF TREE. TREE IRRIGATION SHALL BE PRAY OR ROTOR HEADS SHALL BE ON POI IN 4' OF TREE. TREE IRRIGATION SUSTEM PER THE CO CATE SPRAY HEADS 24" FROM NON-PERN PTION ALLOWED IF ADJACENT SURFACE IN SONSOR TO PROVIDE WEATHER BASED IN ACTOR NOTHERS BASED ON WEATHER. SA GER OR EQUIVALENT. E PLANTING AND IRRIGATION SYSTEM SHALL DOCATE SPRAY HEADS 24" FROM NON-PERN PTION ALLOWED IF ADJACENT SURFACE IN NATION RUNTIMES BASED ON WEATHER. SA GER OR EQUIVALENT. E PLANTING AND IRRIGATION SYSTEM SHAL LOPER/BUILDER PRIOR TO THE CLOSE OF PROJECT OR PHASE. TY DAYS AFTER	TINUOUS UNDER ALL TRENG TO SPACING ON PLANT STO SPACING ON PLANT DECT. IF CONFLICTS ARIS T LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O TO A DEPTH OF 8". APPL ND WITH THE TOP 6" OF S SHALL BE SUPERCEDED F EPORT. IE FOLLOWING PREPAREI IX IS FOR BIDDING PURPO SOIL ANALYSIS REPORT. DUME 10-11B. PER C.Y. OF MIX ER THAN 25% WHERE THE PE E USED FOR WATER FEAT BE APPLIED ON ALL EXPON AREAS, CREEPING OR RO TIONS WHERE MULCH IS R IN THE TOP 6 INCHES OI ER 1,000 SQUARE FEET OF INCHES INTO THE SOIL. INT HE TOP 6 INCHES OI ER 1,000 SQUARE FEET OF INCHES INTO THE SOIL. INTS OF THE WATER EFFIC CAPE DOCUMENTATION P/ H. IGNED RIIT APPLICANT MUST PR DMPLETION, CERTIFICATE NDSCAPE AND IRRIGATION RIGATION SYSTEM. CONTI 'E AND IRRIGATION DAMA APE CONDITION WITH A F CONTAINED CONDITIONS. UP STREAM BUBBLERS, M E ON A SEPARATE VALVE. P-UPS: 6" FOR LAWN, LOW JB AREAS. HEADS ON RIS SPACE FOR POP-UPS. /IOUS PAVING TO PREVEN SPACE FOR POP-UPS.
GROU 13. T HEAD AREA FAILU 14. A ORGA OF 10 AMEN 15. F USED 16. TU IS AL 17. RE 18. A SUPE 16. TU IS AL 17. RE 18. A SUPE 10. FO RATE SUPE 10. FO SUPE 10. FO S	MENCEMENT OF WORK TO COORDINATE F SROUNDCOVER PLANTING SHALL BE CON- JNDCOVER SHALL BE PLANTED ACCORDIN- TREES SHALL BE LOCATED A MINIMUM OF VERS, AND OTHER TREES WITHIN THE PRC S AND PLANS, CONTRACTOR TO CONTAC INTRACTORS LIEABILITY TO RELOCATE TH ALL PLANTING AREAS SHALL BE LOOSENEL ANIC AMENDMENT AND 15 LBS. -10-10 FERTILIZER PER 1000 S.F. AND BLEI JOMENT IS FOR BIDDING PURPOSES, AND DMMENDATIONS OF THE SOIL ANALYSIS RI- TOR BACKFILL IN THE PLANTERS. THIS M RCEDED BY RECOMMENDATIONS OF THE SITE SOIL - 6 PARTS BY VOLUME ORGANIC AMENDMENT - 4 PARTS BY VC SOIL CONDITIONER / FERTILIZER 10-10- IRON SULFATE - 2 LBS. PER C.Y.OF MIX JRF IS NOT ALLOWED ON SLOPES GREATE JJACENT TO AN IMPERMEABLE HARDSCAFE ECIRCULATING WATER SYSTEMS SHALL B MINIMUM 3-INCH LAYER OF MULCH SHALL ACES OF PLANTING AREAS EXCEPT TURF JNDCOVER, OR DIRECT SEEDING APPLICA OF A MINIMUM OF FOUR CUBIC YARDS PL LBE INCORPORATED TO A DEPTH OF SIX ARGEE TO COMPLY WITH THE REQUIREMEN NANCE AND SUBMIT A COMPLETE LANDSC PLYS WITH THE PERFORMANCE APPROAC COF A MINIMUM OF FOUR CUBIC YARDS PL LBE INCORPORATED TO A DEPTH OF SIX ARGEE TO COMPLY WITH THE REQUIREMEN NANCE AND SUBMIT A COMPLETE LANDSC PLYS WITH THE PERFORMANCE APPROAC COF A MINIMUM OF FOUR CUBIC YARDS PL DITRACTOR IS TO AUGMENT EXISTING IRI IR OR REPLACE ANY EXISTING LANDSCAP PLAY OR ROTOR HEADS SHALL BE ON POIL DOCATE SPRAY HEADS 24" FROM NON-PERY PTON ALLOWED IF ADJACENT SUFFICIENT IRREGATION SYSTEM PER THE C CL NEW TREES REQUIRE INDIVIDUAL POP-I IN 4" OF TREE. TREE IRRIGATION SYSTEM SHALL DOCATE SPRAY HEADS 24" FROM NON-PERY PTION ALLOWED IF ADJACENT SUFFICIENT INCLORGY IRRIGATION. ROTATOR OR ROTA AG. DISTRACTOR SHALL REPLACE ANY EXISTING ED CAR OVERHANG AREAS, 12" FOR SHRING WED ADJACENT TO WALLS WITH LIMITED DATA ON THE SASED ON WEATHER. SA GER OR EQUIVALENT. E PLANTING AND IRRIGATION SYSTEM SHALL LOPER/BUILDER PRIOR TO THE CLOSE OF FROJECT OR PHASE. TY DAYS AFTER TLANDSCAPE AND IRRIGA TO THE COSE OF AND ALL OTHER PLANS FOR A ATION INI	TINUOUS UNDER ALL TRENG TO SPACING ON PLANT 5' FROM WALLS, OVERHEL DECT. IF CONFLICTS ARIS T LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O TO A DEPTH OF 8". APPL ND WITH THE TOP 6" OF S SHALL BE SUPERCEDED F EPORT. TE FOLLOWING PREPAREI IX IS FOR BIDDING PURPOR SOIL ANALYSIS REPORT. DLUME 10-1LB. PER C.Y. OF MIX ER THAN 25% WHERE THE PE E USED FOR WATER FEAT BE APPLIED ON ALL EXPONNE AREAS, CREEPING OR RO TIONS WHERE MULCH IS R IN THE TOP 6 INCHES OIL ER 1,000 SQUARE FEET OF INCHES INTO THE SOIL. SITS OF THE WATER EFFIC CAPE DOCUMENTATION P/ H. SIGNED RIGATION SYSTEM. CONTINE CONTAINED CONDITIONS. UP STREAM BUBBLERS, M E ON A SEPARATE VALVE. P-UPS: 6" FOR LAWN, LOW UB AREAS. HEADS ON RIS SPACE FOR POP-UPS. /IOUS PAVING TO PREVEN SPACE FOR POP-UPS.
GROU 13. THEADA FAILUI 14. A COMPACE 15. FUSED 16. TU 15. FUSED 16. TU 17. RE 18. A SUPPE 16. TU 17. RE 18. A SUPPE 16. TU 19. FC SHAL 20. I A ORDIN COMPACE 19. FC SHAL 20. I A ORDIN COMPACE 10. COMPACE 10. COMP	MENCEMENT OF WORK TO COORDINATE F SROUNDCOVER PLANTING SHALL BE CON- JNDCOVER SHALL BE PLANTED ACCORDIN TREES SHALL BE LOCATED A MINIMUM OF PERS, AND OTHER TREES WITHIN THE PRC S AND PLANS, CONTRACTOR TO CONTAC IRE TO MAKE SUCH CONFLICTS KNOWN TO INTRACTORS LIEABILITY TO RELOCATE THAN ALL PLANTING AREAS SHALL BE LOOSENEL NIC AMENDMENT AND 15 LBS. -10-10 FERTILIZER PER 1000 S.F. AND BLEI JOMENT IS FOR BIDDING PURPOSES, AND DMMENDATIONS OF THE SOIL ANALYSIS RI- FOR BACKFILL IN THE PLANTERS. THIS M (SCEDED BY RECOMMENDATIONS OF THE SITE SOIL - 6 PARTS BY VOLUME ORGANIC AMENDMENT - 4 PARTS BY VC SOIL CONDITIONER / FERTILIZER 10-10- IRON SULFATE - 2 LBS. PER C.Y.OF MIX URF IS NOT ALLOWED ON SLOPES GREATE DACENT TO AN IMPERMEABLE HARDSCAF ECIRCULATING WATER SYSTEMS SHALL B MINIMUM 3-INCH LAYER OF MULCH SHALL ACES OF PLANTING AREAS EXCEPT TURF JNDCOVER, OR DIRECT SEEDING APPLICA OR SOILS LESS THAN 6% ORGANIC MATTE OF A MINIMUM OF FOUR CUBIC YARDS PE L BE INCORPORATED TO A DEPTH OF SIX IGREE TO COMPLY WITH THE REQUIREME NANCE AND SUBMIT A COMPLETE LANDSC PLYS WITH THE PERFORMANCE APPROAC CASIOLS OF PLANTING AREAS EXCEPT TURF ONTRACTOR IS TO AUGMENT EXISTING LANDSCAP INFORMENTY WITH A CERTIFICATE OF COMPLY AND SUBMIT A COMPLETE LANDSC PLYS WITH THE PERFORMANCE APPROAC CASIOLS LESS THAN 6% ORGANIC MATTE ON SCHEDULE AND SCHEDULE OF LAN STRAUCTION TO AN ACCEPTABLE LANDSC PLYS WITH THE PERFORMANCE APPROAC CASION SCHEDULE AND SCHEDULE OF LAN STRAUCTION TO AN ACCEPTABLE LANDSC PLYS WITH THE PERFORMANCE APPROAC CASION SCHEDULE AND SCHEDULE OF LAN SCHEDULE AND SCHEDULE OF LAN SCHEDULE AND SCHEDULE OF LANDSC PLYS WITH A CERTIFICATE OF COMPLETION THE PERFORMANCE APPROAC PLYS WITH A CERTIFICATE OF COMPLETION THE PERFORMANCE APPROAC DISTACTOR SHALL REPLACE ANY EXISTING ENCORPORTY WITH A CERTIFICATE OF COMPLETION TO AN ACCEPTABLE LANDSC DISTACTOR SHALL REPLACE ANY EXISTING ENCON TO POVIDE WEATHER BASED IN ATION NUNTIMES BASED ON WEATHER.S AGER OR EQUIVALENT. E PLANTING AND ALL OT	TINUOUS UNDER ALL TRENG TO SPACING ON PLANT S' FROM WALLS, OVERHE, DECT. IF CONFLICTS ARIS T LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O TO A DEPTH OF 8". APPL ND WITH THE TOP 6" OF S SHALL BE SUPERCEDED F EPORT. IE FOLLOWING PREPAREI IX IS FOR BIDDING PURPO SOIL ANALYSIS REPORT. DLUME 10-1LB. PER C.Y. OF MIX ER THAN 25% WHERE THE E. E USED FOR WATER FEAT BE APPLIED ON ALL EXPO AREAS, CREEPING OR RO TIONS WHERE MULCH IS R IN THE TOP 6 INCHES OI ER 1,000 SQUARE FEET OF INCHES INTO THE SOIL. TIS OF THE WATER EFFIC CAPE DOCUMENTATION P/H. IGNED RIGATION SYSTEM. CONTINE APPLETION, CERTIFICATE IDSCAPE AND IRRIGATION RIGATION SYSTEM. CONTINE APPLETION, CERTIFICATE IDSCAPE AND IRRIGATION RIGATION SYSTEM. CONTINE CONTAINED CONDITIONS. UP STREAM BUBBLERS, M E ON A SEPARATE VALVE. P-UPS: 6" FOR LAWN, LOW UB AREAS. HEADS ON RIS SPACE FOR POP-UPS. /IOUS PAVING TO PREVEN S PERMEABLE OR IF USIN RY HEADS MAYBE LOCAT MG IRRIGATION CONTROLL IFORMATIONTHAT WILL AU CALL TRESS AND IRRIGATION ALL BE COMPLETED BY THE F ESCROW OF 50 PERCEN ATION INSTALLATION, THE UN INSTALLATION, THE UN INSTALLATION, THE INTE SPERTED PREVENTION ON TROLL IFORMATION THAT WILL AU CE ALL TRESS AND IRRIGATION ALL BE COMPLETED BY THE F ESCROW OF 50 PERCENTION ALL BE COMPLETED PREVENTION ALL ATTERS AND IRRIGATION ALL BE COMPLETED PREVENTION
GROU 13. THAREAL IN CO 14. A AGE 15. FE 15. FE 16. TH 17. RE 18. A 19. FC 19. FC 19. FC 10. IA 10. IA 1	MENCEMENT OF WORK TO COORDINATE F SROUNDCOVER PLANTING SHALL BE CON- JNDCOVER SHALL BE PLANTED ACCORDIN- TREES SHALL BE LOCATED A MINIMUM OF PERS, AND OTHER TREES WITHIN THE PRC S AND PLANS, CONTRACTOR TO CONTAC IRE TO MAKE SUCH CONFLICTS KNOWN TO NTRACTORS LIEABILITY TO RELOCATE THAN ALL PLANTING AREAS SHALL BE LOOSENEL DATE TO MAKE SUCH CONFLICTS KNOWN TO NTRACTORS LIEABILITY TO RELOCATE THAN ALL PLANTING AREAS SHALL BE LOOSENEL DATE TO MAKE SUCH CONFLICTS KNOWN TO NTRACTORS LIEABILITY TO RELOCATE THAN ALL PLANTING AREAS SHALL BE LOOSENEL DATE TO FERTILIZER PER 1000 S.F. AND BLEL DOMENT SFOR BIDDING PURPOSES, AND DAMENDATIONS OF THE SOIL ANALYSIS RI FOR ALL TREES AND SHURB PLANTING, THIS INCEDED BY RECOMMENDATIONS OF THE SITE SOIL - 6 PARTS BY VOLUME ORGANIC AMENDMENT - 4 PARTS BY VC SOIL CONDITIONER / FERTILIZER 10-10- IRON SULFATE - 2 LBS. PER C.Y.OF MIX USES IN CONDITIONER / FERTILIZER 10-10- IRON SULFATE - 2 LBS. PER C.Y.OF MIX USES THAN 6% ORGANIC MATTE OF A MINIMUM 3-INCH LAYER OF MULCH SHALL ACES OF PLANTING AREAS EXCEPT TURF INDCOVER, OR DIRECT SEEDING APPLICA DR SOILS LESS THAN 6% ORGANIC MATTE OF A MINIMUM OF FOUR CUBIC YARDS PE L BE INCORPORATED TO A DEPTH OF SIX INFREE TO COMPLY WITH THE REQUIREMENT NANCE AND SUBMIT A COMPLETE LANDSC PLYS WITH THE PERFORMANCE APPROAC COMPLY WITH A CERTIFICATE OF CAN ANTOC AND SUBMIT A COMPLETE LANDSC PLYS WITH THE PERFORMANCE APPROAC COMPLY WITH A CERTIFICATE OF CAN ATION NOTES DNTRACTOR IS TO AUGMENT EXISTING IRI IR OR REPLACE ANY EXISTING LANDSCAP STRAUCTION TO AN ACCEPTABLE LANDSC PROYOR ROTOR HEADS SHALL BE ON POI IED CAR OVERHANG AREAS, 12" FOR SHRIW WED ADJACENT TO WALLS WITH LIMITED DOTATE SPRAY HEADS 24" FROM NON-PERS INTRACTOR SHALL REPLACE ANY EXISTING SENSOR TO PROVIDE WEATHER BASED IN ATION RUNTIMES BASED ON WEATHER. SIGNED ATION RUNTIMES BASED ON WEATHER. SHALL DOPARENTIAL COMPLETION (1 E DEVELOPER/BUILDER SHALL BE AND SCHED SHALL DOTATE OF SUBSTANTIAL COMPLETION (1 E DEVELOPER/BUILDER SHALL GUARA	TINUOUS UNDER ALL TRENG TO SPACING ON PLANT S' FROM WALLS, OVERHE, DECT. IF CONFLICTS ARIS T LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O TO A DEPTH OF 8". APPL ND WITH THE TOP 6" OF S SHALL BE SUPERCEDED F EPORT. IE FOLLOWING PREPAREI IX IS FOR BIDDING PURPO SOIL ANALYSIS REPORT. DLUME 10-1LB. PER C.Y. OF MIX ER THAN 25% WHERE THE E. E USED FOR WATER FEAT BE APPLIED ON ALL EXPO AREAS, CREEPING OR RO TIONS WHERE MULCH IS R IN THE TOP 6 INCHES OI ER 1,000 SQUARE FEET OF INCHES INTO THE SOIL. TIS OF THE WATER EFFIC CAPE DOCUMENTATION P/H. IGNED RIGATION SYSTEM. CONTINE APPLETION, CERTIFICATE IDSCAPE AND IRRIGATION RIGATION SYSTEM. CONTINE APPLETION, CERTIFICATE IDSCAPE AND IRRIGATION RIGATION SYSTEM. CONTINE CONTAINED CONDITIONS. UP STREAM BUBBLERS, M E ON A SEPARATE VALVE. P-UPS: 6" FOR LAWN, LOW UB AREAS. HEADS ON RIS SPACE FOR POP-UPS. /IOUS PAVING TO PREVEN S PERMEABLE OR IF USIN RY HEADS MAYBE LOCAT MG IRRIGATION CONTROLL IFORMATIONTHAT WILL AU CALL TRESS AND IRRIGATION ALL BE COMPLETED BY THE F ESCROW OF 50 PERCEN ATION INSTALLATION, THE UN INSTALLATION, THE UN INSTALLATION, THE INTE SPERTED PREVENTION ON TROLL IFORMATION THAT WILL AU CE ALL TRESS AND IRRIGATION ALL BE COMPLETED BY THE F ESCROW OF 50 PERCENTION ALL BE COMPLETED PREVENTION ALL ATTERS AND IRRIGATION ALL BE COMPLETED PREVENTION
GROU 13. THAREAL IN CO 14. A AGE 14. A AGE 15. FE 15. FE 15. FE 16. TH 17. RE 18. A 19. FC 19. FC 19. FC 19. FC 19. FC 19. FC 19. FC 19. FC 19. FC 19. FC 10. I A 10. I	MENCEMENT OF WORK TO COORDINATE F SROUNDCOVER PLANTING SHALL BE CON JNDCOVER SHALL BE PLANTED ACCORDIN TREES SHALL BE LOCATED A MINIMUM OF JERS, AND OTHER TREES WITHIN THE PRO SAND PLANS, CONTRACTOR TO CONTAC IRE TO MAKE SUCH CONFLICTS KNOWN TO INTRACTORS LIEABILITY TO RELOCATE TH ALL PLANTING AREAS SHALL BE LOOSENEL INIC AMENDMENT AND 15 LBS. -10-10 FERTILIZER PER 1000 S.F. AND BLEI DOMENT IS FOR BIDDING PURPOSES, AND DIMENDATIONS OF THE SOIL ANALYSIS RI COR ALL TREES AND SHURB PLANTING, TH STE SOIL - 6 PARTS BY VOLUME ORGANIC AMENDMENT - 4 PARTS BY VOLUME ORGANIC AMENDMENT - 4 PARTS BY VOLUME ORGANIC AMENDMENT - 4 PARTS BY VOLUME SITE SOIL - 6 PARTS BY VOLUME ORGANIC AMENDMENT - 4 PARTS BY VOL SOIL CONDITIONER / FERTILIZER 10-10- IRON SULFATE - 2 LBS. PER C.Y. OF MIX JRF IS NOT ALLOWED ON SLOPES GREATE DIACENT TO AN IMPERMEABLE HARDSCAF ECIRCULATING WATER SYSTEMS SHALL B MINIMUM 3-INCH LAYER OF MULCH SHALL ACES OF PLANTING AREAS EXCEPT TURF JNDCOVER, OR DIRECT SEEDING APPLICA OR SOILS LESS THAN 6% ORGANIC WATTE OF A MINIMUM OF FOUR CUBIC YARDS P L BE INCORPORATED TO A DEPTH OF SIX AGREE TO COMPLY WITH THE REQUIREMEN NANCE AND SUBMIT A COMPLETE LANDSC PLYS WITH THE PERFORMANCE APPROAC 	TINUOUS UNDER ALL TRENGTO SPACING ON PLANT 5' FROM WALLS, OVERHE, DJECT. IF CONFLICTS ARIS T LANDSCAPE ARCHITECT 0 THE LANDSCAPE ARCHITECT 0 THE LANDSCAPE ARCHITECT 0 THE LANDSCAPE ARCHITECT 0 THE LANDSCAPE ARCHITECT 0 TO A DEPTH OF 8". APPL ND WITH THE TOP 6" OF S SHALL BE SUPERCEDED F EPORT. IE FOLLOWING PREPAREI IX IS FOR BIDDING PURPO SOIL ANALYSIS REPORT. DLUME 10-1LB. PER C.Y. OF MIX ER THAN 25% WHERE THE PE E USED FOR WATER FEAT BE APPLIED ON ALL EXPC AREAS, CREEPING OR RC TIONS WHERE MULCH IS R IN THE TOP 6 INCHES OIL ER 1,000 SQUARE FEET OF INCHES INTO THE SOIL. ENTS OF THE WATER EFFIC CAPE DOCUMENTATION P/ H. IGNED RIIT APPLICANT MUST PR DMPLETION, CERTIFICATE IDSCAPE AND IRRIGATION RIGATION SYSTEM. CONTI 10 STREAM BUBBLERS, M E ON A SEPARATE VALVE. P-UPS: 6" FOR LAWN, LOW JB AREAS. HEADS ON RIS SPACE FOR POP-UPS. /IOUS PAVING TO PREVEN S PACE FOR POP-UPS. /IOUS PAVING TO PREVEN S PERMEABLE OR IF USIN RY HEADS MAYBE LOCAT NG IRRIGATION CONTROLLI IFORMATIONTHAT WILL AU E ALL TRESS AND IRRIGATION E ALL TRESS AND IRRIGATION E ALL TRESS AND IRRIGATION E AREQUIRED ON ALL SPRIF E ORDINANCE AND APPLIF
GROU 13. THAREAL IN CO 14. AC AGE 15. FE 15. FE 16. TH 17. RE 16. AL 17. RE 18. A 19. FC 19. FC 10. IA 10. IA	MENCEMENT OF WORK TO COORDINATE F SROUNDCOVER PLANTING SHALL BE CON JNDCOVER SHALL BE PLANTED ACCORDIN TREES SHALL BE LOCATED A MINIMUM OF VERS, AND OTHER TREES WITHIN THE PRO S AND PLANT. CONTACTOR TO CONTAC IRE TO MAKE SUCH CONFLICTS KNOWN TO INTRACTORS LIEABILITY TO RELOCATE TH ALL PLANTING AREAS SHALL BE LOOSENEL MIC AMENDMENT AND 15 LBS. 10-10 FERTILIZER PER 1000 S.F. AND BLEI IDMENT IS FOR BIDDING PURPOSES, AND MMENDATIONS OF THE SOIL ANALYSIS RI COR ALL TREES AND SHURB PLANTING, TH 9 FOR BACKFILL IN THE PLANTERS. THIS M RCEDED BY RECOMMENDATIONS OF THE SITE SOIL - 6 PARTS BY VOLUME ORGANIC AMENDMENT - 4 PARTS BY VOL SOIL CONDITIONER / FERTILIZER 10-10- IRON SULFATE - 2 LBS. PER C.Y.OF MIX JRF IS NOT ALLOWED ON SLOPES GREATE DJACENT TO AN IMPERMEABLE HARDSCAF ECIRCULATING WATER SYSTEMS SHALL B MINIMUM 3-INCH LAYER OF MULCH SHALL ACES OF PLANTING AREAS EXCEPT TURF INDCOVER, OR DIRECT SEEDING APPLICA OR SOILS LESS THAN 6% ORGANIC MATTE OF A MINIMUM OF FOUR CUBIC YARDS PE L BE INCORPORATED TO A DEPTH OF SIX VARCE TO COMPLY WITH THE REQUIREME NANCE AND SUBMIT A COMPLETE LANDSC 2/LYS WITH THE PERFORMANCE APPROAC MICON SCHEDULE AND SCHEDULE OF LAN STAUCTION TO AN ACCEPTABLE LANDSC 2/LYS WITH THE PERFORMANCE APPROAC MICON SCHEDULE AND SCHEDULE OF LAN STAUCTION TO AN ACCEPTABLE LANDSC 2/LYS WITH THE PERFORMANCE APPROAC MICON SCHEDULE AND SCHEDULE OF LAN STAUCTION TO AN ACCEPTABLE LANDSC 2/LYS WITH THE PERFORMANCE APPROAC CONTRACTOR IS TO AUGMENT EXISTING IRI IN 4' OF TREE. TREE IRRIGATION SYSTEM PER THE C ATION NOTES DNTRACTOR SHALL REPLACE ANY EXISTING SENSOR TO PROVIDE WEATHER BASED IN ATION RUNTIMES BASED ON WEATHER. S MORTACTOR SHALL SUBMIT TO THE HOMEO IFICATE OF SUBSTANTIAL COMPLETION (1 ED EAVELOPER/BUILDER SHALL BE ON PORY 100 AGY IRRIGATION. ROTATOR OR ROTA 4.0. DNTRACTOR SHALL SUBMIT TO THE COSE OF ROLATE OF AUGENTIAL COMPLETION (1 ED EVELOPER/BUILDER SHALL SUMANTER XMONTHS AND ALL OTHER PLANS FOR A ATION INSTALLATION. ESSURE REGULATING DE	TINUOUS UNDER ALL TRENON TO SPACING ON PLANT S' FROM WALLS, OVERHE, DJECT. IF CONFLICTS ARIS T LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHITECT O THE LANDSCAPE ARCHI IE MATERIALS. D TO A DEPTH OF 8". APPL ND WITH THE TOP 6" OF S SHALL BE SUPERCEDED F EPORT. E FOLLOWING PREPAREI IX IS FOR BIDDING PURPO SOIL ANALYSIS REPORT. DLUME 10-1LB. PER C.Y. OF MIX ER THAN 25% WHERE THE PE E USED FOR WATER FEAT BE APPLIED ON ALL EXPO AREAS, CREEPING OR RC TIONS WHERE MULCH IS R IN THE TOP 6 INCHES OI ER 1,000 SQUARE FEET OF INCHES INTO THE SOIL. INTS OF THE WATER EFFIC APE DOCUMENTATION P/ H. GGNED RIIT APPLICANT MUST PR DMPLETION, CERTIFICATE NDSCAPE AND IRRIGATION RIGATION SYSTEM. CONTI 'E AND IRRIGATION WITH A F CONTAINED CONDITIONS. UP STREAM BUBBLERS, M E ON A SEPARATE VALVE. P-UPS: 6" FOR LAWN, LOW JB AREAS. HEADS ON RIS SPACE FOR POP-UPS. /IOUS PAVING TO PREVEN S PERMEABLE OR IF USIN RRY HEADS MAYBE LOCAT VIOUS PAVING TO PREVEN S PERMEABLE OR IF USIN RRY HEADS MAYBE LOCAT VIOUS PAVING TO PREVEN S PERMEABLE OR IF USIN RRY HEADS MAYBE LOCAT VIOUS PAVING TO PREVEN S PACE FOR POP-UPS. /IOUS PAVING TO PREVEN S PACE FOR POP-UPS. /IOUS PAVING TO PREVEN S PACE FOR POP-UPS. /IOUS PAVING TO PREVEN S PERMEABLE OR IF USIN RRY HEADS MAYBE LOCAT VION INSTALLATION, THE WINERS/PROPERTY OWNI 2.40 G LAMC.) E ALL TRESS AND IRRIGATION IF OR AN A SEPARATE PRESSUF THE SPECIFIED IRRIGATION ALL BE COMPLETED BY TH S ESCROW OF 50 PERCEN
GROU 13. THARAC INCOMPACE 14. ACC 14. ACC 15. FL 15. FL 16. THAN 15. FL 16. THAN 17. RE 18. ACC 19. FL 19. FL 10. IA 10. IA 10	MENCEMENT OF WORK TO COORDINATE F SROUNDCOVER PLANTING SHALL BE CON JNDCOVER SHALL BE PLANTED ACCORDIN TREES SHALL BE LOCATED A MINIMUM OF HERS, AND OTHER TREES WITHIN THE PRO S AND PLANS, CONTRACTOR TO CONTAC INTRACTORS LIEABILITY TO RELOCATE TH ANC AMENDMENT AND 15 LBS. 10-10 FERTILIZER PER 1000 S.F. AND BLEI JDMENT IS FOR BIDDING PURPOSES, AND JMMENDATIONS OF THE SOIL ANALYSIS RI TOR ALL TREES AND SHURB PLANTING, TH FOR BACKFILL IN THE PLANTERS. THIS MIC COMPLIES IN PLANTING AREAS STIES SOIL - 6 PARTS BY VOL SOIL CONDITIONER / FERTILIZER 10-10- IRON SULFATE - 2 LBS. PER C.Y.OF MIX JRF IS NOT ALLOWED ON SLOPES GREATE JJACENT TO AN IMPERMEABLE HARDSCAF ECIRCULATING WATER SYSTEMS SHALL B MINIMUM 3-INCH LAYER OF MULCH SHALL ACES OF PLANTING AREAS EXCEPT TURF INDCOVER, OR DIRECT SEEDING APPLICA DR SOILS LESS THAN 6% ORGANIC MATTE OF A MINIMUM OF FOUR CUBIC YARDS PE L BE INCORPORATED TO A DEPTH OF SIX IGREE TO COMPLY WITH THE REQUIREMENDANCE AND SUBMIT A COMPLETE LANDSCAP PLYS WITH THE PERFORMANCE APPROAC COMPLAY WITH A CERTIFICATE OF COMPLAND SUBMIT A COMPLETE LANDSCAP DNTRACTOR IS TO AUGMENT EXISTING IRI IR OR REPLACE ANY EXISTING LANDSCAP DYTRACTOR IS TO AUGMENT EXISTING IRI IR OR REPLACE ANY EXISTING LANDSCAP DYTRACTOR IS TO AUGMENT EXISTING IRI IR OR REPLACE ANY EXISTING LANDSCAP DYTRACTOR IS TO AUGMENT EXISTING IRI IN OR REPLACE ANY EXISTING LANDSCAP DYTRACTOR SHALL REPLACE ANY EXISTING EXAL OF TREE. TREE IRRIGATION SYSTEM PER THE COMPLAND TO AN ACCEPTABLE LANDSCAP DYTRACTOR SHALL REPLACE ANY EXISTING ENCOR PORVIDE WEATHER BASED IN ATION RUNTIMES BASED ON WEATHER.S GER OR EQUIVALENT. E PLANTING AND IRRIGATION SYSTEM SHALL EDVELOPER/BUILDER SHALL GUARANTER X MONTHS AND ALL OTHER PLANS FOR A ATION RUNTIMES BASED ON WEATHER.S GER OR EQUIVALENT. E PLANTING AND IRRIGATION SYSTEM SHALL EDVELOPER/BUILDER SHALL GUARANTER SUBSURE REGULATING DEVICES ARE REQU EDVELOPER/BUILDER SHALL GUARANTER ATION INSTALLATION. ESSURE REGULATING DEVICES ARE REQU EDVELOPER/BUILDER S	TINUOUS UNDER ALL TRENG TO SPACING ON PLANT 5' FROM WALLS, OVERHE, DJECT. IF CONFLICTS ARIS T LANDSCAPE ARCHITECT 0 THE LANDSCAPE ARCHITECT 0 THE LANDSCAPE ARCHITECT 0 THE LANDSCAPE ARCHITECT 10 TO A DEPTH OF 8". APPL ND WITH THE TOP 6" OF S SHALL BE SUPERCEDED F EPORT. 10 FOLLOWING PREPAREN 11 S FOR BIDDING PURPOC SOIL ANALYSIS REPORT. 12 IS FOR BIDDING PURPOC SOIL ANALYSIS REPORT. 14 STOR BIDDING PURPOC SOIL ANALYSIS REPORT. 15 SFOR BIDDING PURPOC 16 THAN 25% WHERE THE 16. 17 UNDE 10-1LB. PER C.Y. OF MIX 18 THAN 25% WHERE THE 19. 19. 19. 19. 19. 19. 19. 10. 19. 19. 19. 19. 10. 10. 10. 10. 10. 10. 10. 10

4. AN IRRIGATION AUDIT REPORT SHALL BE COMPLETED AT THE TIME OF

	_	
IDENTIAL FOUR G. MC 12.22A.25		•
E, ENCLOSURE / ELECTRICAL /		
LTI-FAMILY)
LAT		
	Y	
TER" SPACING ARE CING GIVEN. VERIFY QUIREMENTS.		90245
THE ARCHITECT ON		undo, ca
SS THAN 90 DAYS CE SHALL INCLUDE	C	109 eucalyptus drive, el segundo, ca 90245 [o] 310.322.3700
ONTRACT THE SITE AT ALL TIMES		/ptus driv 2.3700
LISTED FOR L HAVE PRIORITY		109 eucalyptus ([o] 310.322.3700
ER THAN 1" IN RIOR TO PLANTING. PIT DIMENSIONS, SOIL		
RCHITECT PRIOR TO	RAMSE	ARCHIERA
HE APPROVAL OF	(((★ (No. 0	C-34257 31/19
RIOR TO SCHEDULES. EES AND SHRUBS. IT LEGEND.		CALIFORM
EADS, WALKS, SE BETWEEN SIZE OF CT FOR RESOLUTION. HITECT WILL RESULT		
PLY 4 C.Y. OF SOIL. THIS	ISANI PL CA 90291	
ED SOIL MIX SHALL BE		
OSES, AND SHALL BE		
E TOE OF THE SLOPE	2308 /ENICE	
TURES.	Щ ~ Щ >	
OSED SOIL ROOTING S CONTRAINDICATED.		Schodula
OF SIL, COMPOST AT A	Revision Revision Number	Revision Date
ICIENT LANDSCAPE PACKAGE THAT		
– ROVIDE THE OWNER E OF INSTALLATION, IN MAINTENANCE.		
TRACTOR SHALL AGED FROM FULLY FUNCTIONAL		
MIN. 2 PER TREE,		
W GROUNDCOVER OR SERS ARE ONLY		
ENT OVERSPRAY. NG ALTERNATIVE TED 12" FROM		
LLER WITH A MODULE AUTOMATE THE C, RAINBIRD ET	LANDSC	APE PLAN
HE NT OF THE UNITS OF	DRAWN	CR
E LANDSCAPE NERS ASSOCIATION A	CHECKED	PNK
ATION FOR A PERIOD ER LANDSCAPE AND	DATE	06/22/2021
IRE IS BELOW OR ON DEVICES.	SCALE	AS NOTED
INKLER HEADS	JOB #	16080
IED THEM FOR THE		
BE KEPT WITH THE		00
D BY EITHER THE LANS, OR THE	L1	.00
F FINAL INSPECTION.		